

Product datasheet

Specifications



APC Back-UPS Connect 12Vdc
36W, lithium-ion, mini network ups
to protect internet routers, IP
cameras and more

CP12036LI

Overview

Lead time Usually in Stock

Main

Main Input Voltage	12 V DC
Product or component type	Uninterruptible power supply (UPS)
Main Output Voltage	12 V DC
Battery type	Li-Ion (Lithium-Ion)

Complementary

Number of tare power 2 W

Batteries & Runtime

Battery recharge time 9 h

Physical

Colour	White
Width	99 mm
Depth	109 mm
Product weight	300 g
Mounting mode	Not rack-mountable
Height	25 mm

Output

Maximum configurable power in W	36 W
output voltage	12 V

Conformance

Product certifications	CE
Standards	CE EN/IEC 61000-4-8 EN/IEC 61000-4-2 EN/IEC 62368-1

Environmental

ambient air temperature for operation	0...40 °C
relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-10...50 °C
Storage altitude	0...5000 m
IP degree of protection	< IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.300 cm
Package 1 Width	11.500 cm
Package 1 Length	16.300 cm
Package 1 Weight	366.000 g
Unit Type of Package 2	S02
Number of Units in Package 2	10
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.900 kg
SCC14	10731304632396

Contractual warranty

Warranty	24 months
----------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	73b1309a-d65b-4414-9fb4-d80a65253bd6
China RoHS Regulation	China RoHS declaration

Use Again

 Repack and remanufacture	
Removable battery	Yes
Take-back	No