

Data Sheet

Momentus® Thin

The World's First 7mm, 2.5 Inch Form Factor Drive

Key Advantages

- 7mm z-height form factor enables thin chassis design for all segments of laptop computing
- Seagate SmartAlign[™] technology provides a transition to 4K sectors without the need for software utilities¹
- Self-Encrypting Drives mitigate data breaches, comply with data protection regulations and preserve brand recognition¹
- Self-Encrypting Drives with FIPS 140-2 certification are approved by the US and Canadian governments^{1,2}

Best-fit Applications

- Entry-level to high-performance laptops enjoy a stylish, thin and lightweight design without exceeding your budget
- Netbooks have a thinner netbook without compromising on storage or affordability
- Ultraportables take advantage of a stylish, thin and lightweight design without compromising on features
- Slim consumer electronics devices add some style to your digital life

² See FIPS 140-2 Level 2 Certificate at http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401vend.htm



¹ Refer to specifications table for further information and feature options.

Momentus® Thin



The World's First 7mm, 2.5 Inch Form Factor Drive

Seagate clearly demonstrates how to differentiate, increase profitability and meet market demand for slim computing.

- The 2.5 inch form factor enables compromise-free, costeffective and reliable storage for slim entry-level laptops, high-end netbooks, ultraportables and CE devices.
- Seagate® Momentus® Thin drives come in 500, 320, 250 and 160GB capacities, to provide the right capacity points for fullfunctioning computing devices. For performance enthusiasts, take a look at the 7,200 RPM Momentus Thin drive.
- Users now have 16MB of cache on both the mainstream 5,400 RPM and the high-performance 7,200 RPM options.
- Seagate Self-Encrypting Drives (SEDs) deliver US-governmentgrade encryption without performance degradation – protecting your data where it lives.
- The Momentus Thin SED is the first Trusted Computing Group Opal specification drive to achieve FIPS 140-2, Level-2 certification by the US and Canadian governments.

| Specifications | Momentus 5400 Drives | | | | Momentus 7200 Drives | | |
|--|-------------------------|--|--|-------------------------|-------------------------|-------------------------|-------------------------|
| | 500GB ¹ | 320GB1 | 250GB1 | 160GB ¹ | 320GB1 | 250GB1 | 160GB ¹ |
| Feature Options | | | | | | | |
| Standard Models | ST500LT012 ² | ST320LT020 ² ST320LT012 ³ | ST250LT003 ² ST250LT012 ³ | ST160LT003 ² | ST320LT007 ² | ST250LT007 ² | ST160LT007 ² |
| Self-Encrypting Drive Models | ST500LT025 ³ | | | | ST320LT014 ² | ST250LT014 ² | |
| Self-Encrypting Drive FIPS 140-2 Validated | ST500LT015 ³ | | | | ST320LT009 ² | ST250LT009 ² | |
| Interface | SATA 3Gb/s NCQ | SATA 3Gb/s NCQ | SATA 3Gb/s NCQ | SATA 3Gb/s NCQ | SATA 3Gb/s NCQ | SATA 3Gb/s NCQ | SATA 3Gb/s NCQ |
| Cache (MB) | 16 | 16 | 16 | 16 | 16 | 16 | 16 |
| Configuration | | | | | | | |
| Bytes per Sector | 4,096 | 4,096 | 4,096 | 4,096 | 4,096 | 4,096 | 4,096 |
| Reliability/Data Integrity | | | | | | | |
| Head-Rest Method | QuietStep™ Ramp Load | QuietStep Ramp Load | QuietStep Ramp Load | QuietStep Ramp Load | QuietStep Ramp Load | QuietStep Ramp Load | QuietStep Ramp Load |
| Load/Unload Cycles | >600,000 | >600,000 | >600,000 | >600,000 | >600,000 | >600,000 | >600,000 |
| Non-recoverable Read Errors per Bits Read | 1 per 10 ¹⁴ | 1 per 10 ¹⁴ | 1 per 10 ¹⁴ | 1 per 10 ¹⁴ | 1 per 10 ¹⁴ | 1 per 10 ¹⁴ | 1 per 10 ¹⁴ |
| Annualised Failure Rate (AFR) | 0.48% | 0.48% | 0.48% | 0.48% | 0.48% | 0.48% | 0.48% |
| Power Management | | | | | | | |
| Power (W) Seek, Typical Idling, Typical | 1.2 0.45 | 1.4 0.48 | 1.4 0.48 | 1.4 0.48 | 1.6 0.66 | 1.6 0.66 | 1.6 0.66 |
| Environmental | | | | | | | |
| Temperature (°C) Operating Non-operating | 0 to 60 -40 to 70 | 0 to 60 -40 to 70 | 0 to 60 -40 to 70 | 0 to 60 -40 to 70 | 0 to 60 -40 to 70 | 0 to 60 -40 to 70 | 0 to 60 -40 to 70 |
| Shock (Gs) Operating: 2ms Non-operating: 1ms | 400 1,000 | 350 1,000 | 350 1,000 | 350 1,000 | 350 1,000 | 350 1,000 | 350 1,000 |
| Acoustics (bels — sound power) Idling, Typical Seek, Typical | 2.0 2.2 | 2.0 2.2 | 2.0 2.2 | 2.0 2.2 | 2.3 2.5 | 2.3 2.5 | 2.3 2.5 |
| Physical | | | | | | | |
| Height (in/mm) | 0.276/7.0 | 0.276/7.0 | 0.276/7.0 | 0.276/7.0 | 0.276/7.0 | 0.276/7.0 | 0.276/7.0 |
| Vidth (in/mm) | 2.76/70.1 | 2.76/70.1 | 2.76/70.1 | 2.76/70.1 | 2.76/70.1 | 2.76/70.1 | 2.76/70.1 |
| Depth (in/mm) | 3.959/100.55 | 3.959/100.55 | 3.959/100.55 | 3.959/100.55 | 3.959/100.55 | 3.959/100.55 | 3.959/100.55 |
| Weight (lb/g) | 0.203/92.0 | 0.203/92.0 | 0.203/92.0 | 0.203/92.0 | 0.203/92.0 | 0.203/92.0 | 0.203/92.0 |
| Carton Unit Quantity | 50 | 50 | 50 | 50 | 50 | 50 | 50 |
| Cartons per Pallet | 60 | 60 | 60 | 60 | 60 | 60 | 60 |
| Cartons per Layer | 10 | 10 | 10 | 10 | 10 | 10 | 10 |

¹ One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

www.seagate.com











AMERICAS ASIA/PACIFIC Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000 Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888 Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 41 86 10 00

² Advanced Format 4K sector drive with SmartAlign™ technology resolves misalignment conditions.

³ SmartAlign technology is not available on this model.