

Silent Series R2

40mm



- Speed: 4000 +/- 10%
- Dimensions (mm): 40 x 40 x 10
- Weight (g): 18.1
- Cable length (mm): 400 +/- 10mm
- Number of blades: 7
- Connector: 3-Pin fan header
- Starting voltage: < 9
- Max. airflow (CFM): 4.53
- Max. pressure (mm H2O): 1.95
- Noise level (dBA): 18.0

EAN/GTIN-13: 7350041080725 UPC: 817301010726
Product code: FD-FAN-SSR2-40

80mm



- Speed: 1400 +/- 10%
- Dimensions (mm): 80 x 80 x 25
- Weight (g): 65.9
- Cable length (mm): 400 +/- 10mm
- Number of blades: 7
- Connector: 3-Pin fan header
- Starting voltage: < 6
- Max. airflow (CFM): 19.5
- Max. pressure (mm H2O): 0.97
- Noise level (dBA): 14.3

EAN/GTIN-13: 7350041080756 UPC: 817301010757
Product code: FD-FAN-SSR2-80

140mm



- Speed: 800 +/- 200RPM
- Dimensions (mm): 140 x 140 x 25
- Weight (g): 149.0
- Cable length (mm): 500 +/- 10mm
- Number of blades: 11
- Connector: 3-Pin fan header
- Starting voltage: < 11
- Max. airflow (CFM): 52.8 **with Low Speed adapter**
- Max. pressure (mm H2O): 0.54
- Noise level (dBA): 14.9

EAN/GTIN-13: 7350041080787 UPC: 817301010788
Product code: FD-FAN-SSR2-140

50mm



- Speed: 3500 +/- 10%
- Dimensions (mm): 50 x 50 x 10
- Weight (g): 20.7
- Cable length (mm): 400 +/- 10mm
- Number of blades: 7
- Connector: 3-Pin fan header
- Starting voltage: < 9
- Max. airflow (CFM): 7.64
- Max. pressure (mm H2O): 1.74
- Noise level (dBA): 20.0

EAN/GTIN-13: 7350041080732 UPC: 817301010733
Product code: FD-FAN-SSR2-50

92mm



- Speed: 1300 +/- 10%
- Dimensions (mm): 92 x 92 x 25
- Weight (g): 84.2
- Cable length (mm): 400 +/- 10mm
- Number of blades: 7
- Connector: 3-Pin fan header
- Starting voltage: < 6
- Max. airflow (CFM): 24.6
- Max. pressure (mm H2O): 0.60
- Noise level (dBA): 12.5

EAN/GTIN-13: 7350041080763 UPC: 817301010764
Product code: FD-FAN-SSR2-92

EFS fan accessory

Rubber mountings for fans. A cheap and effective way to decrease noise caused by vibrations.

EAN/GTIN-13: 7350041080046
Product code: FD-AC-EFS



60mm



- Speed: 3000 +/- 10%
- Dimensions (mm): 60 x 60 x 25
- Weight (g): 56.1
- Cable length (mm): 400 +/- 10mm
- Number of blades: 7
- Connector: 3-Pin fan header
- Starting voltage: < 6
- Max. airflow (CFM): 20
- Max. pressure (mm H2O): 2.89
- Noise level (dBA): 17.4

EAN/GTIN-13: 7350041080749 UPC: 817301010740
Product code: FD-FAN-SSR2-60

120mm



- Speed: 850 +/- 200RPM
- Dimensions (mm): 120 x 120 x 25
- Weight (g): 113.3
- Cable length (mm): 500 +/- 10mm
- Number of blades: 11
- Connector: 3-Pin fan header
- Starting voltage: < 11
- Max. airflow (CFM): 28.8 **with Low Speed adapter**
- Max. pressure (mm H2O): 0.54
- Noise level (dBA): 12.0

EAN/GTIN-13: 7350041080770 UPC: 817301010771
Product code: FD-FAN-SSR2-120



All fans are delivered with 4pcs of metal screws and from 60mm and bigger sizes 4pcs rubber screws are also included. The electrical cable is sleeved, to make it easier to work with. The 120mm and 140mm fans come with a low-speed adapter, which lets you choose between two different rotation speeds without a separate fan controller




Case fans


Silent Series R2

	40mm	50mm	60mm	80mm	92mm	120mm		140mm	
Speed	4000 +/- 10%	3500 +/- 10%	3000 +/- 10%	1400 +/- 10%	1300 +/- 10%	850 +/-200RPM	1200 +/- 10%	800 +/-200RPM	1000 +/- 10%
Dimensions (mm)	40x40x10	50x50x10	60x60x25	80x80x25	92x92x25	120x120x25		140x140x25	
Weight (g)	18.1	20.7	56.1	65.9	84.2	113.3		149.0	
Cable length (mm)	400 +/- 10	400 +/- 10	400 +/- 10	400 +/- 10	400 +/- 10	500 +/- 10		500 +/- 10	
Number of blades	7	7	7	7	7	11		11	
Starting voltage	< 9	< 9	<6	<6	<6	<11	<6	<11	<6
Max. airflow (CFM)	4.53	7.64	20	19.5	24.6	28.8	40.6	52.8	66.0
Max. Pressure (mm H ₂ O)	1.95	1.74	2.89	0.97	0.60	0.54	1.07	0.54	0.84
Noise level (dBA)	18	20	17	14	13	12	15	15	19
Connector	3-pin	3-pin	3-pin	3-pin	3-pin	3-pin		3-pin	
Accessories	Metal Screws	Metal Screws	Metal Screws Rubber Screws	Metal Screws Rubber Screws	Metal Screws Rubber Screws	Metal Screws Rubber Screws Low Speed Adapter		Metal Screws Rubber Screws Low Speed Adapter	


Using the Rubber Screws




1
Insert the rubber screws into the fan screw holes on your case, with the hexagonal heads the outside



2
Pull the rubber screws so that the inner rings on the rubber screws goes through the fan screw holes



3
Place the fan on the rubber screws



4
Pull the rubber screw so that the edge on the beveled part of the rubber screw gets through the fan frame. TIP: It's easier to get a grip on them with pliers!

Fractal Design brings you scandinavian design and quality in a box

www.fractal-design.com