









Device Specifications	Phaser 6020	Phaser 6022	WorkCentre 6025	WorkCentre 6027	
Output Speed			<u>'</u>		
<b>Colour</b> A4 / 210 x 297 mm	Up to 10 ppm	Up to 18 ppm	Up to 10 ppm	Up to 18 ppm	
<b>Black and White</b> A4 / 210 x 297 mm	Up to 12 ppm	Up to 18 ppm	Up to 12 ppm	Up to 18 ppm	
Monthly Duty Cycle <sup>1</sup>	Up to 30,000 pages / month	Up to 30,000 pages / month			
Recommended Average Monthly Print Volume <sup>2</sup>	Up to 1,500 pages				
Memory	128 MB	256 MB		512 MB	
Processor	525 MHz				
Connectivity	Wi-Fi b/g/n Wi-Fi Direct High speed USB 2.0	10/100Base-TX Ethernet Wi-Fi b/g/n Wi-Fi Direct High speed USB 2.0	Wi-Fi b/g/n Wi-Fi Direct High speed USB 2.0	10/100Base-TX Ethernet Wi-Fi b/g/n Wi-Fi Direct High speed USB 2.0	
Paper Handling					
Automatic Document Feeder (ADF	<del>-</del> )				
Capacity <sup>3</sup>	NA		Platen	15 sheets	
Sizes			Up to 216 x 297 mm	Custom Sizes: 148 x 210 mm to 216 x 356 mm	
Weights			NA	60 to 105 gsm	
Bypass Tray					
Capacity <sup>3</sup>	NA		10 sheets	NA	
Sizes	_		Custom Sizes: 76 x 127 mm to 216 x 356 mm		
Weights			60 to 163 gsm		
Media Types			Plain Bond Lightweight Card Stock Lightweight Glossy Card Stock Envelopes Labels Recycled Plain-Reloaded Bond-Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloaded Recycled-Reloaded		
Main Tray					
Capacity <sup>3</sup>	150 sheets				
Sizes	Sizes: 76 x 127 mm to 216 x 356	mm			
Weights	60 to 163 gsm				

Media Types	Plain Bond Lightweight Card Stock Lightweight Glossy Card Stock Envelopes Labels Recycled Plain-Reloaded Bond-Reloaded Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Reloa	nded			
Paper Output					
Output Capacity <sup>3</sup>	100 sheets (face-down)				
Print	Phaser 6020	Phaser 6022	WorkCentre 6025	WorkCentre 6027	
First-page-out Time	As fast as 19 seconds colour / 19 seconds black and white	As fast as 13 seconds colour / 12 seconds black and white	As fast as 19 seconds colour / 19 seconds black and white	As fast as 13 seconds colour / 12 seconds black and white	
Resolution	Up to 1200 x 2400 dpi enhanced in	Up to 1200 x 2400 dpi enhanced image quality			
Maximum Print Area	4.0 mm from all edges				
Page Description Languages	GDI, PDF Direct, TIFF, JPEG	PostScript 3 compatible PCL® 5c, 6, PDF Direct, TIFF, JPEG	GDI, PDF Direct, TIFF, JPEG	PostScript 3 compatible PCL® 5c, 6, PDF Direct, TIFF, JPEG	
	Colour Balance Adjust PANTONE® Colour Calibrated Solid-c Auto Screening (Standard, Fineness Manual Duplex N-up Watermark Custom Page Sizes Fit to Page Scaling Reduce/Enlarge Draft Mode Collation Bidirectional Print Drivers Job Monitoring				
Mobile Printing	Apple® AirPrint™ Xerox® PrintBack	Apple® AirPrint™ Xerox® PrintBack Google Cloud Print	Apple® AirPrint™ Xerox® PrintBack	Apple® AirPrint™ Xerox® PrintBack Google Cloud Print	
Operating Systems	Microsoft® Windows® 7 (32-/64-bit), 8 (32-/64-bit), 8.1 (32-/64-bit), XP (32-/64-bit via Windows v3 driver only), 2003 Server (32-/64-bit), Windows Server 2008 (32-/64-bit), Windows Server 2012 (64-bit), Windows server 2012 (64-bit), Windows server 2012 R2 (64-bit), Vista (32-/64-bit) Mac OS® 10.5.8, 10.6.x, 10.7.x, 10.8.x, 10.9.x Red Hat® Enterprise Linux 6 Desktop (32-/64-bit) SUSE® Linux Enterprise Desktop 11 (32-/64-bit) Ubuntu® 12.04 (32-/64-bit)				
Network Protocols	NA Scan to Email, Scan to SMB (SMB/SMB2 Client), LDAP for Address Book			SMB2 Client), Scan to FTP (FTP Client),	
		Wired: 10/100 BaseT TCP/IP: IPsec, IPsec (IKE) / Pre-Shared Key SNMPv3	NA NA	Wired: 10/100 BaseT TCP/IP: IPsec, IPsec (IKE) / Pre-Shared Key SNMPv3, Kerberos	
		including DHCP/BOOTP/RARP/AutoIP) /UDP, SMTP/POP3, Email Alert, HTTP,			
Font Capability	NA	81 PostScript fonts 81 PCL fonts 16 PDF fonts	NA	81 PostScript fonts 81 PCL fonts 16 PDF fonts	

Сору	Phaser 6020	Phaser 6022	WorkCentre 6025	WorkCentre 6027
Colour Speed	NA			
A4 / 210 x 297 mm			Up to 10 ppm	Up to 18 ppm
Black and White Speed A4 / 210 x 297 mm			Up to 12 ppm	Up to 18 ppm
Document Scanner			Platen	Automatic Document Feeder with 15-sheet capacity
Document Scanner Size			Up to 216 x 297 mm	Up to 216 x 356 mm
Sides (input:output)			1:1	
Quantity			1 to 99	
Resolution			Up to 600 x 600 dpi	
First-copy-out Time			As fast as 40 seconds colour / 24 seconds black and white	As fast as 30 seconds colour / 20 seconds black and white
Copy Features			Reduce/Enlarge (25% - 400%) Lighter/Darker Sharpness Colour Balance Auto Exposure ID Card Copy Edge Erase Collate	
Scan	Phaser 6020	Phaser 6022	WorkCentre 6025	WorkCentre 6027
Capability	NA		Colour, Greyscale and Black and Wh	nite Scanning
Input Speed – Black and White			Platen only	Scan up to 14 ipm – A4
Input Speed – Colour			Platen only	Scan up to 9 ipm - A4
Resolution (maximum)			200 dpi 300 dpi 600 dpi 1200 dpi (TWAIN only)	200 dpi 300 dpi 600 dpi 1200 dpi (TWAIN only)
Bit Depth			24-bit Colour, 8-bit Greyscale, 1-bit Lineart	24-bit Colour, 8-bit Greyscale, 1-bit Lineart
Maximum Scan Areα			Platen: Up to 216 x 297 mm	ADF: Up to 216 x 356 mm
Network Filing Protocol			FTP SMB/SMB2 SMTP/POP3	
File Formats			Image-only PDF TIFF JPEG	
Supported Scan Destinations			Scan to Network Computer (SMB/ F Scan to Email (SMTP/POP3) WSD Application (TWAIN USB/Network), Mac 10.6 or later (USB/Network/Ma USB	WIA (USB/WSD Scan)
Fax	Phaser 6020	Phaser 6022	WorkCentre 6025	WorkCentre 6027
	Pilaser 6020	Pridser 6022	WorkCentre 6025	WorkCentre 6027
Walk-up Fax <sup>4</sup>				22.6 1/1
Fax Speed	NA -			33.6 Kbps
Memory				2 MB
Resolution				Up to 406 x 392 dpi (Super-High Image Quality) Up to 203 x 392 dpi (Super Fine) Up to 203 x 196 dpi (High Quality) Up to 203 x 98 dpi (Standard)
Compression				MH/MR/MMR/JBIG/ 1-bit compression
Walk-up Fax Features				Auto Redial Auto Resend Auto Reduction One-touch dial (Up to 8) Address book (Up to 99 address entries) Group faxing (Up to 6) Delayed Start Cover page Junk Fax Filter Fax Forward (Forward, Print & Forward, Email, Email and Print, Forward to Server, Forward to Server and Print)

Security				
Security Features	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 WEP (64-/128-bit) WPA2-PSK (AES) and WPA/WPA2-PSK (Mixed Mode)	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 SNMP v3 IPsec WEP(64-/128-bit) WPA2-PSK (AES) and WPA/WPA2-PSK (Mixed Mode)	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 WEP (64-/128-bit) WPA2-PSK (AES) and WPA/WPA2-PSK (Mixed Mode) Network Address Book Authentication (LDAP, Windows Kerberos)	Secure HTTPS (SSL/TLS) Secure IPP SSL IP Filtering IPv6 SNMP v3 IPsec WEP(64-/128-bit) WPA2-PSK (AES) and WPA/WPA2-PSK (Mixed Mode) Network Address Book Authentication (LDAP, Windows Kerberos)
Wi-Fi Security			'	,
	WEP(64-/128-bit)     WPA2-PSK (AES)     WPA/WPA2-PSK (Mixed Mode)			
Device Management				
Xerox® CentreWare® Internet Servi	ces			
Device Status	Web server embedded  Tray status/contents Consumables status			
Print Queue Viewing	Visibility of current and completed jobs			
Job Submission	Print-ready files (PDF, TIFF, JPEG)		Print-ready files (PS, PCL® 5c/6, PDF,	TIFF, JPEG)
Device Administration	Allows remote installation, setting of configuration options and management of the device			
Browsers	Users can access the Embedded We	b Server of the machine using a gener	rally available web browser.	
Xerox® Mobile Solutions				
Xerox® PrintBack	based mobile device. When you're v	vorking offsite or away from your desk fault printer back at your office or des	s them beyond your computer and out c and receive an important document v ik. Plus, it supports the most common o	via your mobile device, simply
Power Consumption	Phaser 6020	Phaser 6022	WorkCentre 6025	WorkCentre 6027
220-240 VAC, 50/60 Hz, 5A				
Continuous Printing (average)	220 watts	340 watts	220 watts	330 watts
Standby Mode	45 watts or less			
Low Power Mode	10 watts or less			
Sleep Mode	3.5 watts or less			
Operating Environment				
Temperature	10° to 32°C			
Humidity	10% to 85%			
<b>Sound Pressure</b> Printing Standby	49.1 dB(A) or less 21.9 dB(A) or less			
Warm-up Time (from Power Save)	Less than 35 seconds			
Dimensions and Weight (Unpackaged)	Width	Depth	Height	Weight
Phaser 6020	394 mm	304 mm	234 mm	10.9 kg
Phaser 6022	397 mm	398 mm	246 mm	12.4 kg
WorkCentre 6025	410 mm	389 mm	318 mm	14.5 kg
	410 mm	439 mm	388 mm	16.9 kg
WorkCentre 6027				
WorkCentre 6027  Dimensions and Weight (Packaged)	Width	Depth	Height	Weight
Dimensions and Weight		Depth 393 mm	Height 388 mm	Weight 12.6 kg
Dimensions and Weight (Packaged)	Width			
Dimensions and Weight (Packaged) Phaser 6020	Width 481 mm	393 mm	388 mm	12.6 kg

#### Regulatory Compliance / Certifications

#### Regulatory Compliance

EN 60950-1:2006 2nd Edition / IEC 60950-1:2005 2nd Edition

CE marked

Low Voltage Directive 2006/95/EC EMC Directive 2004/108/EC EN 55022, Class B EN 55024

REACH Directive 1907/2006 R&TTE Directive 1995/5/EC RoHS Directive 2011/65/EU WEEE Directive 2012/19/EU

EU Commission Regulation 1275/2008 as amended by (EU) No 801/2013 (ErP Lot 26)

EN 300328 / 301893 (European WiFi)

#### Certifications

ENERGY STAR® Microsoft WHQL GS Mark

Xerox Green World Alliance USB 2.0 Hi-Speed

Wi-Fi Certified Apple® AirPrint Apple Universal Binaries

Apple Bonjour® Google Cloud Print™

IPv6 Ready

To view the latest list of certifications, go to www.xerox.com/OfficeCertifications.

#### What Comes in the Box

- Phaser 6020 Colour Printer or Phaser 6022 Colour Printer or WorkCentre 6025 Colour Multifunction Printer or WorkCentre 6027 Colour Multifunction Printer
- Toner Cartridge (500 page capacity<sup>5</sup>)
- Quick Installation Guide, Quick Use Guide, Software and Documentation Disc
- Power Cable
- USB Cable

#### Supplies and Options

Toner	Cartridges
-------	------------

Description	Part Number
Black: 2,000 standard pages <sup>s</sup>	106R02759
Cyan: 1,000 standard pages <sup>5</sup>	106R02756
Magenta: 1,000 standard pages <sup>s</sup>	106R02757
Yellow: 1,000 standard pages <sup>5</sup>	106R02758

Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.



<sup>&</sup>lt;sup>2</sup> Expected regular monthly throughput. <sup>3</sup> Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

<sup>&</sup>lt;sup>4</sup> Requires analogue phone line. <sup>5</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.