





B246HYLAymidr PRODUCTIVITY, HIGH TECHNOLOGIES	
 <b>PURE ACCURACY</b>	  
Sub Model Product line	B246HYLA B6 Series
<i>General</i>	
Display Type	Flat screen/TFT
Dimensions WxHxD (mm)	554.4x379-529x221.2
Min. Profile Thickness (mm)	19
Net Weight (kg)	6.42
Gross Weight (kg)	8.32
Chassis colour and finish	Darkgrey Matt
<i>Display</i>	
Panel Technology	IPS
Crystalbrite	No
Size cm	60
Size Inch	23.8
Format	16:9
Display dimensions (mm)	527x296
Pixel Pitch (mm)	0.2745
Resolution	1920x1080@60Hz
Frequency (H/V)	30-80kHz/55-75Hz
PPI	93
Rsp time (ms)	5ms (G2G)
Dynamic Contrast ratio	100M:1
Brightness (cd/m2)	250
H/V° CR 10:1	178/178
H/V° CR 5:1	178/178
Colors	16.7M
Bit	6Bit+Hi-FRC
NTSC Color Gamut	72% NTSC
Backlight type	LED
Screen coating hardness	3H
OS Compliance	Win10 compliant
<i>Video Input</i>	
VGA	1xVGA
DVI	1xDVI
HDMI	1xHDMI
<i>Audio Input</i>	
Audio line	Audio In
Speaker	2Wx2
<i>Ergonomics</i>	
VESA Wall Mounting	100x100
Kensington Support	Yes
Tilt	-5°~35°
Swivel degrees	+/-60°
Hgt Adj (mm)	150
Pivot degrees	90
<i>Power Supply</i>	
Power Supply	Internal
Power Switch	Yes
Energy Star Type	ES7.0
Off/Standby (W)	0.35
Sleep (W)	0.45
Min On (W)	23
Max (W)	-
EEL Class	<b>B</b>
Power On (W)	27
Annual Energy Consumption (kWh/year)	40
Mercury (mg)	0
Lead	Presence*
<i>Manufacturer Guarantee</i>	
Warranty	EMEA Commercial (3yr)
Certificates	CE, TÜV GS, ISO9241-307 class I
Certification	TCO7.0
MTBF Hours @ 25°C	30000
<i>Pallet and Container Loading</i>	
Pallet qty (pcs)	50
Pallet Size WxHxD (cm)	120.3x101.1x225
Container loading 20"/40"	500/1050
Package Dimensions (cm)	61.7x42.2x19
Included cables	VGA, DVI
<i>Special Features</i>	
Wide Viewing Angle	Wide Viewing Angle
ComfyView	ComfyView