G2590PX



24.5 inch (62.2 cm) LCD MONITOR





ЛОС

1ms Response Time

A pixel response time of 1ms GTG means speed without the smear for an enhanced experience. Fast-moving action and dramatic transitions will be rendered

smoothly without the effects of ghosting.



144Hz Refresh Rate

Equip yourself with twice the frame rate of other monitors and say goodbye to image stuttering and

blurry motion. With a 144Hz refresh rate every frame is rendered sharply and in smooth succession, so you can line up your shots accurately and appreciate high speed races in all their glory.



FreeSync

Whatever your setup, achieve the highest framerate and smoothest display possible via AMD Free-Sync Technology. Whether you're dashing through explosions or screeching around rain

slicked bends, wave goodbye to screen tearing and lag – and leave your opponents in your smoothly rendered dust.



Shadow Control

Bring the battle out of the shadows with Shadow Control! Brighten dark areas or sink them back into blackness on the fly, without affecting the rest of the display.

Screen Details

Resolution	1920x1080 PX
Refresh rate	144Hz
Response time	1 ms
Panel	TN
Backlight	WLED
sRGB Coverage (%)	96
FlickerFree	Yes
Aspect ratio	16:9
Brightness (typical)	400 cd/m ²
Contrast (dynamic)	50M:1
Contrast (static)	1000:1
Pixel Pitch (H) (V)	0.2832
Diagonal (inch)	24.5 inch
Active Screen Area (HxW)	543.74x302.62 mm
Viewing angle (CR10)	170/160 [°]
Display Colours	16.7 Million
Panel Finishing	Matt
Adobe RGB Coverage (%)	84
OSD languages	English, French , Spanish, Portuguese, German, Italian, Dutch, Swedish, Finnish, Polish ,Czech, Russian, Korean, Traditional Chinese, Simple Chinese, Japanese
Ultra-wide screen	No
Connections	
Signal Input	VGA;DisplayPort 1.2 x 1;HDMI 1.4 x 2
USB input	USB 3.0 x 4

What's in the box

Built-in Speakers

VGA cable (1,8 m), HDMI cable (1,8 m), Displayport Cable (1,8 m), Audio Cable (1,8 m), Power Cable C7 (1.8 m),

2 W x 2

Sustainability

- · Environmental and energy: RoHS, Lead-free, Mercury Free
- Recyclable packaging material: 100 %

Ergonomics	
Pivot	1
Swivel	-45/45 °
Tilt	-3.5 / 19.5 °
Height Adjust Amount	130mm
Removable Stand	1
Vesa Wallmount	100x100
Power details	
Powersupply	Internal
Powersource	100 - 240V 50/60Hz
Power Consumption	On 28 wattW, Off 0.5 wattW Standby 0.5 wattW,
Dimensions	
Product Dimensions (incl base)	558.6x199.5x513.2 mm
CartonDimensions	626x203x417 mm
Net Weight (excl package)	5.43 Kg
Gross Weight (incl package)	7.75 Kg
Warranty	
WarrantyPeriod	3 Years
EAN	4038986166096
MTBF	50.000 hours
Begulations	

Regulations

TUV-GS , TUV-Bauart 1, CE 1, TCO no, Energystar No, EPEAT No, FCC , EAC 1, ISO 9241-307 class I 1, Rohs compliant 1,

