

HD143X Big Screen Entertainment



- Lights on viewing 3200 ANSI Lumens
- Amazing colour accurate Rec.709 colours
- Easy connectivity 2x HDMI, MHL, USB Power
- Clear, powerful audio 10W speaker

The Full HD 1080p HD143X projector is ideal for watching live sport, TV shows or movies any time of day. You can even connect your games console and play games on it with its low input latency. Convenient and easy to set up this bright and versatile projector also boasts Amazing colour technology and conforms to Rec.709 delivering accurate true to life colour reproduction.

An integrated speaker provides you with great sound and two HDMI inputs enables an easy setup. Perfect for connecting a laptop, PC, Bluray player, media streamer or games console. You can even turn it into a smart projector by connecting a HDMI dongle like the Google Chromecast[™], Amazon Fire TV or Apple TV[™] to play games, stream videos and share photos on the big screen in the comfort of your own home.

Weighing less than 2.5kg you can take it round to a friend's house with the optional carry bag for a sports event, movie night or games marathon for the best big screen experience anywhere with a flat surface.

Specifications

-	
Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	3,200 lumens
Contrast ratio	23,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction - vertical	40
Uniformity	80%
Screen size	0.71m - 7.65m (28in - 301in)(Diagonal)
Lamp info	
Light source	Lamp
Lamp watts	240
Lamp life (hours)	3500 (Bright), 12000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.47:1 - 1.62:1
Projection distance (m)	1m - 9.8m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	15.59 ~ 17.14
Native offset	116%
Connectivity	
Connections	Insute 1 v HDMI 1 40 2D outport + MHL 1 v HDMI 1 40
	Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x 3D sync, 1 x 12V trigger
	Source I V OD SALO, I V IZV miggor
-	
	25 10
Noise level (typical)	25dB
Noise level (typical) PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
General Noise level (typical) PC compatibility 2D compatibility	
Noise level (typical) PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,
Noise level (typical) PC compatibility 2D compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
Noise level (typical) PC compatibility 2D compatibility 3D compatibility	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side-1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Side-by-Side:108050 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish,
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 France Pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080p(50/60Hz) Side-by-Side-1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord, remote control, Battery, basic user manual
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (standby)	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (standby) Power consumption (max)	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz SECAM B/D/G/K/K11/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (standby) Power consumption (max) Weight and dimensions	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (Traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W 295W
Noise level (typical) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (standby) Power consumption (max)	 FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H///M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480//p, 576i/p, 720p(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz) Sida-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D Security bar, Kensington Lock, Password protected interface 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Backlit home remote 1 10W AC power cord, remote control, Battery, basic user manual 100 ~ 240V, 50 ~ 60Hz 0.5W





Copyright © 2018, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 25092018030812