

OVERVIEW

1. Card reader	5. USB-C 2.0 (data transfer / PD only) *
2. USB 3.2 Gen 1	6. HDMI
3. USB 3.2 Gen 1 (Always On)	7. USB-C 3.2 Gen 2
4. Power connector *	8. Headphone / microphone combo jack (3.5mm)

Notes:

- Ports with * are only available on selected models
- Port 5 (not shown on the sample product above) is mutually exclusive with Port 4

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 5 / 7 Processor

Processor**^[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
AMD Ryzen 5 6600HS Creator Edition	6	12	3.3GHz	4.5GHz	3MB L2 / 16MB L3	LPDDR5-6400	AMD Radeon™ 660M Graphics
AMD Ryzen 7 6800HS Creator Edition	8	16	3.2GHz	4.7GHz	4MB L2 / 16MB L3	LPDDR5-6400	AMD Radeon 680M Graphics

Notes:

- The maximum supported memory speed will vary on the selected onboard memory

Operating System

Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 Home 64 Single Language
- No operating system

Graphics

Graphics**^[1]

Graphics	Type	Memory	Key Features
AMD Radeon 660M	Integrated	Shared	DirectX® 12
AMD Radeon 680M	Integrated	Shared	DirectX 12
NVIDIA® GeForce GTX 1650 Laptop GPU	Discrete	4GB GDDR6	Advanced Optimus, Dynamic Boost 2.0, DirectX 12
NVIDIA GeForce RTX™ 3050 Laptop GPU	Discrete	4GB GDDR6	Advanced Optimus, Resizable BAR, Dynamic Boost 2.0, NVIDIA DLSS, DirectX 12 Ultimate
NVIDIA GeForce RTX 3050 Ti Laptop GPU	Discrete	4GB GDDR6	Advanced Optimus, Resizable BAR, Dynamic Boost 2.0, NVIDIA DLSS, DirectX 12 Ultimate

Notes:

- For Dynamic Boost 2.0, this function is only supported under NVIDIA GeForce Laptop GPU and 120Hz display panels.

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI supports up to 4096x2160@30Hz
- USB-C supports up to 5120x2800@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

16GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type

LPDDR5-6400

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^[1]

One drive, up to 512GB M.2 2242 SSD or 1TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe® Gen 4x4 slot, supports M.2 2242/2280 SSD

Storage Type**

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe NVMe®, PCIe 4.0 x4	512GB
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4	512GB / 1TB

Notes:

1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

Removable Storage

Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, optimized with Dolby® Atmos®

Microphone^[1]

Dual array microphone with noise-cancelling, support Lenovo Voice Assistant (LVA), and Amazon Alexa

Camera

IR & FHD 1080p hybrid, fixed focus, with ToF sensor

Notes:

1. Amazon Alexa might be limited by country-level restrictions.

Sensor

Sensors

- Hall sensor
- ToF sensor

Battery

Battery^[1]

Integrated Li-Polymer 75Wh battery, supports Rapid Charge Express (get 3 hours of runtime with a 15-minute charge)

Max Battery Life^[2]

- Discrete graphics models:
MobileMark® 2018@200nits: 9.45 hr
Local video (1080p) playback@150nits: 13.57 hr
- Integrated graphics models:
MobileMark 2018@200nits: 14.61 hr
Local video (1080p) playback@150nits: 22.97 hr

Notes:

1. Rapid Charge Express is only affected as hibernate or fully shut down the computer
2. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0,

continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**^[1]

- 100W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 135W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Notes:

1. AC adapter offerings depend on the country.

DESIGN

Display

Display**^{[1][2]}

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
16.0"	2.5K (2560x1600)	None	IPS	350 nits	Anti-glare	16:10	1200:1	100% sRGB	170°	TÜV Low Blue Light, DC Dimming
16.0"	2.5K (2560x1600)	None	IPS	350 nits	Anti-glare	16:10	1200:1	100% sRGB	170°	Refresh rate 120Hz (Max), TÜV Low Blue Light, DC Dimming
16.0"	2.5K (2560x1600)	None	IPS	350 nits	Anti-glare	16:10	1200:1	100% sRGB	170°	Refresh rate 120Hz (Max), G-Sync, TÜV Low Blue Light, DC Dimming

Color Calibration

- T-CON (Timer Control Register) color calibration
- No color calibration

Touchscreen

Non-touch

Notes:

1. California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>
2. 120Hz adaptive refresh rate is available on select models only

Input Device

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight

LED backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical^[1]

Dimensions (WxDxH)

356 x 251 x 16.9 mm (14.02 x 9.88 x 0.67 inches)

Weight

Models	Weight
Discrete graphics models	Around 1.95 kg (4.30 lbs)
Integrated graphics models	Around 1.92 kg (4.23 lbs)

Case Color**

- Cloud grey
- Storm grey

Surface Treatment

Aluminium stamping (anodized)

Case Material

Aluminium (top), aluminium (bottom)

Notes:

1. The system dimensions and weight vary depending on configurations.

CONNECTIVITY

Network

Ethernet

No Ethernet

WLAN + Bluetooth®^{[1][2]}**

- Wi-Fi® 5, 802.11ac 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card

Notes:

1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
2. Intel® Wi-Fi 6 full features might be limited by country-level restrictions.

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 2 (support data transfer, Power Delivery, and DisplayPort™)
- 1x HDMI 2.0
- 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***

- 1x USB-C 2.0 (support data transfer and Power Delivery, models with integrated graphics)
- 1x Power connector (models with discrete graphics)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
USB 2.0: 480 Mbit/s;
USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
Thunderbolt™ 3/4: 40 Gbit/s

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- User password
- Master hard disk password

- User hard disk password
- Self-healing BIOS

Other Security

IR camera for Windows Hello

SERVICE

Warranty

Base Warranty^[1]**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

Notes:

1. More information of warranty policy, please access <https://pcsupport.lenovo.com/warranty>

ENVIRONMENTAL

Operating Environment

Temperature

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant

Other Certifications

Other Certifications

TÜV Rheinland® Low Blue Light (Hardware Solution)

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow

disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD



AMD



AMD



AMD



AMD



AMD