

L130



DATASHEET



The L130 is ideal for home users looking for quality, ultra-low-cost printing. Featuring a high-capacity ink tank system, users can now print more pages at a lower cost. Simple and hassle-free set up helps you get started instantly to maximise productivity and avoid downtime. Epson printhead technology means the L130 consistently produces high-quality, reliable results.

Say goodbye to cartridges

The L130 offers an ultra low-cost per page for both black and colour printing. It comes with enough ink in the box to print up to a massive 4,000 pages in black and 6,500 pages in colour², that's around two years' worth of ink¹, without needing to change an ink cartridge.

Improve productivity

Setting up the L130 is easy and hassle-free so you can start printing straight away. When it's time to refill the inks, fast top-up technology means the job is made simple and quick to reduce downtime. Epson-genuine ink bottles make it easy to refill the ink tank with their clear labelling and drip-free nozzles.

Epson-quality printing

The purpose-built ink tank is fully integrated into the printer and Epson-genuine ink bottles make it easy to refill the ink tank with their clear labelling and drip-free nozzle, so you can enjoy reliable colour printing without the mess. The L130 also comes with a one year or 15,000 page manufacturers warranty for additional piece of mind. Epson's Micro Piezo technology and ISO print speeds of up to 7ppm³ help produce high-quality, consistent results, fast.

KEY FEATURES

- **Ultra-low-cost printing**
Integrated ultra-high-capacity ink tank
- **Two years of ink included¹**
4,000 pages in black and 6,500 pages in colour²
- **High quality, reliable results**
Micro Piezo technology and Epson genuine ink
- **Peace of mind**
Covered by Epson's 12 month or 15,000 page warranty
- **User friendly**
Hassle-free with simple set-up and maintenance



PRODUCT SPECIFICATIONS

TECHNOLOGY

Printing Method	On-demand inkjet (Piezo electric)
Minimum Droplet Size	3 pl, With Variable-Sized Droplet Technology
Ink Technology	Dye Ink
Printing Resolution	5,760 x 1,440 dpi
Nozzle Configuration	180 Nozzles black, 59 Nozzles per colour
Category	Consumer
All-in-One Functions	Print

PRINT

Printing Speed ISO/IEC 24734	7 Pages/min Monochrome, 3.5 Pages/min Color
Maximum Printing Speed	69 Seconds per 10 x 15 cm photo (Epson Premium Glossy Photo Paper), 15 Pages/min Color (plain paper), 27 Pages/min Monochrome (plain paper)
Colours	Magenta, Yellow, Cyan, Black

For detailed information on printing speeds please visit <http://www.epson.eu/testing>.

PAPER / MEDIA HANDLING

Number of paper trays	1
Paper Formats	A4, A5, A6, B5, C6 (Envelope), DL (Envelope), No. 10 (Envelope), Letter, 9 x 13 cm, 10 x 15 cm, 13 x 18 cm, 16:9, User defined, Legal
Duplex	Manual
Paper Tray Capacity	50 Sheets Standard, 50 Sheets maximum, 10 Photo Sheets
Output Tray Capacity	30 Sheets

GENERAL

Energy Use	0.7 W (sleep mode), 9 W (printing), 2.2 W (Ready), 0.3 W (Power off), ENERGY STAR® qualified
Product dimensions	482 x 222 x 130 mm (Width x Depth x Height)
Product weight	2.7 kg
Noise Level	5.2 B (A) with Epson Premium Glossy Photo Paper / Photo RPM mode - 39 dB (A) with Epson Premium Glossy Photo Paper / Photo RPM mode
Compatible Operating Systems	Mac OS X 10.6.8 or later, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Vista, Windows Vista x64, Windows XP, Windows XP x64, XP Professional x64 Edition
Supply Voltage	AC 100 V - 240 V
Interfaces	USB
Power Supply	220V

LOGISTICS INFORMATION

SKU	C11CE58401
EAN code	8715946546773
Multiple Order Quantity	1 Units
Country of Origin	Philippines

L130

WHAT'S IN THE BOX

- 4 x 70ml individual ink bottles (Bk,C,Y,M)
- Warranty document
- Software (CD)
- Setup guide
- Power cable
- Main unit

INK CARTRIDGE COMPATIBILITY

- T6641
- T6642
- T6643
- T6644



INK YIELD DATA



4-colour ink bottles for L-Series T6644

- 4,000 pages*
- 6,500 pages*

* Quoted yields/CPP are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC24712. Quoted yields/CPP are NOT based on ISO/IEC24711. Quoted yields/CPP may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature



* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com
Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04
(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece 210-8099499 Hungary 06800 147 83
Ireland 01 436 7742
Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429
South Africa (+2711) 465-9621
Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal – 0,99 kr/min, Lokala samtäl – 0,30 kr/min, Utlandssamtäl – 0,89 kr/min) Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.

1.) 2 years of ink based upon user's average monthly print volume (IDC WW Page Volume Program, 2013) 2) Quoted yields/CPP are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC24712. Quoted yields/CPP are NOT based on ISO/IEC24711. Quoted yields/CPP may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature 3) Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing

EPSON®