

Key Features

- Built in USB type A for charging
- SuperColor™ technology
- 2W cube speaker
- Immersive 3D viewing
- VGA, Composite and HDMI inputs



Product Description

The ViewSonic PA502XP XGA projector for presentations offers impressive multimedia performance from various devices in small to medium-sized meeting rooms and classrooms. Packed with 3,500 ANSI Lumens of high brightness and SuperColor™ Technology, the projector is guaranteed to project consistent and true-to-life image even in brightly lit environments. It integrates VGA, Composite, HDMI inputs and 2W speaker, fulfilling the needs to project multimedia contents including multimedia devices and online videos. In addition, with the USB Type-A with power supply, it is capable for wireless projection through HDMI wireless dongle for media streaming or mirroring contents from mobile device. This projector also comes with an energy-efficient smart energy feature which reduces power consumption and extends the lamp life to 15,000 hours on average.

SPECIFICATION

Projection System:	0.55" XGA
Native Resolution:	1024x768
DC Type:	DC3
Brightness:	3500
Contrast Ratio with SuperEco Mode:	22000:1
Display Color:	1.07 Billion Colors
Light Source:	Lamp
Light Source Life:	5000/15000
Lamp Watt:	190W
Lens:	F=2.5-2.7, f=22.08-24.28mm
Projection Offset:	125% +/-5%
Throw Ratio:	1.97-2.17
Image Size:	30" - 300"
Throw Distance:	1.16m-13.42m(100" @ 3.97m)
Keystone:	+/- 40° (Vertical)
Optical Zoom:	1.1x
Audible Noise (Normal/Eco):	30dB
Response Time:	16ms
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility:	NTSC, PAL, SECAM
Horizontal Frequency:	15K~102KHz
Vertical Scan Rate:	23~120Hz

INPUT

Computer in (share with component):	1
Composite:	1
Audio-in (3.5mm):	1
HDMI (HDCP):	1 (HDMI 1.4/ HDCP 1.4)

OUTPUT

Audio out (3.5mm):	1
Speaker:	2W
USB Type A (Power):	1 (5V/ 1A)

CONTROL

RS232:	1
USB Type Mini B (Services):	1

OTHERS

Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
Power Consumption:	Normal: 240WStandby: <0.5W
Operating Temperature:	0~40°C
Net Weight:	2.1kg
Dimensions (WxDxH) with Adjustment Foot:	320x210x123mm
Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

STANDARD ACCESSORY

Power Cord:	1
VGA Cable:	1
Remote Control:	1
QSG:	1

OPTIONAL ACCESSORY

Lamp/Light Source:	RLC-111
Carry Bag:	PJ-CASE-008