



Ultra Short Throw Projector for Education

FEATURES

- Ultra short throw lens to make 110 inch screen at only 51cm away
- Size matters: full HD 1080p resolution to show every details from your computer
- 3,500 lumens of brightness, and 10,000:1 contrast ratio for clear, crisp and bright projection
- 2x 10W speakers and microphone input ensure you are clearly heard
- Compatible with NovoConnect collaboration solution to engage students in interactive learning
- Long lasting life with up to 12,000 hours lamp-life
- Eco Friendly and Energy Saving with sleep timer and also auto-power-off when there is no signal input
- Integrated network monitoring and management solutions including Crestron® RoomView™
- 5 year education warranty



Ultra short throw lens can make 110 inch projection screen from as little as 51cm away

The DH772UST is the ultimate interactive ultra-short-throw projector for the education with 3500 lumen of brightness and 1080p resolution. The projector offers a 110" diagonal projection image from as little as 51 cm away from the screen surface and ensures ensure that the sound quality is crisp and clear too, thanks to powerful, in-built 2x10W speakers which, combined with microphone input, ensures teachers and lecturers can be heard clearly.



DH772UST SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	3500 ANSI Lumens
	Native Resolution	1080p (1920x1080)
	Max. Supported Resolution	UHD (3840 x 2160) @60Hz
	Contrast Ratio	10,000:1
	Native Aspect Ratio	16:9
	Keystone Correction	Vertical: +/- 40°
Optical	Throw Ratio	0.33: 1
	Image Size (Diagonal)	88" - 110"
	Projection Distance	341 - 510 mm
	Projection Lens	F = 2.5, f = 5.1 mm
	Zoom Ratio	Fixed 1x
	Offset	124%
Features	Features	NA, 3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock, NA, NA, NA
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x1), HDMI Number of Ports v 2.0 (x2), Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45, RS-232, 3D-Sync, USB A (Power Only), USB B (Service), Microphone (Mini-Jack), NA
General	Lamp Life and Type	6,000 / 12,000 Hours (Normal / Eco. Mode)
	Speakers	10W x 2
	Dimensions (W x D x H)	287.7 x 374.5 x 122.6 mm (not including height of mirror)
	Weight	5 kg
	Noise Level	33dB / 29dB (Normal / Eco. Mode)
	Warranty	Education Warranty: 5 years projector / 3 years on lamp or 2.000 hours whichever comes first
	Standard Accessories	VGA Cable, User Manual (CD), Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811123650-SVV), Universal Wall Mount (T/R 0.35) (%WM-3), Remote Control P/N (5041841300)
	UPC Code	813097024336