## UHZ50 Smart 4K UHD laser home entertainment projector







- True 4K UHD resolution and laser technology -HDR and HLG compatible
- Lights on viewing 3000 lumens of brightness
- Optimised for fast-moving smooth action 16.7ms response time in 4K at 60Hz and 4ms in 1080P at 240Hz
- Flexible and easy installation Four corner correction, 1.3x zoom and vertical lens shift



Get ready for a whole new cinematic experience in the comfort of your own home. The stylish UHZ50 laser projector delivers vivid 4K UHD resolution for incredibly crisp images with exceptional clarity and vibrancy for movies, TV shows, games, and sports. With the included enhanced gaming mode, gamers can enjoy fast-moving action with a 16.7ms response time in 4K at 60Hz and 4ms in 1080P at 240Hz.

Packed with the latest technology and features, this stylish projector boasts HDR and HLG compatibility, three HDMI 2.0 inputs, seamless voice control, streaming apps and a built-in media player. Laser technology provides long-lasting, exceptional colour accuracy with extensive DCI-P3 coverage.

Zoom type     Manual       Focal length (mm)     12.81mm~16.74mm       Lens shift     Vertical +10%       Native offset     105%       Lens shift     Yes - {{downloads_link}}       Connectivity     Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)       Outputs 1 x Audio 3.5mm, 1 x S/PDIF     Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync       General     Yoise level (typical)       Noise level (typical)     27dB       PC compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p(50/60Hz)       3D compatibility     Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Full 3D       Security     Security bar, Kensington Lock, Password protected interface       OSD / display languages     25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,	Specifications	
Resolution of the compatible o	Display/image	
Brightness     3.000 lumms       Contrast ratio     2.500,000:1       Aspect ratio     10:9       Aspect ratio     -compatible       4:3	Display technology	DLP™
Contrast ratio     2,500,000:1       Native aspect ratio     16-3       Aspect ratio     4/3       Keystone correction -     +/40°       Horizontal     -       Respect ratio compatible     4/3       Respect ratio compatible     1073.4       Horizontal scan rate     1073.4       Horizontal scan rate     1073.4       Uniformity     80%       Screen size     0.87m - 7.68m (34.1° - 302.4°) diagonal       Lamp info     Lamp       Lift     30,000 hours       Optical     1.21:1 - 1.59:1       Projection distance (m)     1.21:1 - 1.59:1       Zoom type     Marual       Focal length (mm)     1.21:1 - 1.59:1       Focal length (mm)     1.23:1 mm - 10.74mm       Lens shift     Vertical + 10%       Connections     Inputs 2x HDMI 2.0, 3x USBA.1 x HDMI 2.0 (eAPC)       Outputs 1 x Audio 3.5mm, 1 x SPDIF       Connections     Inputs 2x HDMI 2.0, 3x USBA.1 x HDMI 2.0 (eAPC)       Outputs 1 x Audio 3.5mm, 1 x SPDIF       Noise level (typical)     27dB       Noise level (typical)     29dB       PC compatibility     UHD, FHD, UXAA, SNGA, WXGA, HD, XGA, SVGA, VAGA, Mac       20 compatibility     Side-by-Side 100050-601, 20050/6016, 20050/6016, 20050/6016, 20050/6016, 20050/6016, 20050/6016, 20050/6016, 20050/6016, 20050/6016, 20050/	Resolution	UHD (3840x2160)
Native aspect ratio     16:3       Aspect ratio - compatible     4:3       Keystone correction - + /-4:0°     -       horizontal     -       Keystone correction - vertical     +/-4:0°       Has vertical auto keystone     Yes       Correction     50:75 - 01:148 Kbz       Wetrical scan rate     50:75 - 01:148 Kbz       Unitomity     80%       Screen size     0.87m - 7.68m (34.1* - 302.4*) diagonal       Lamp info     Laser       LASER life     30,000 hours       Optical     Throw ratio       Throw ratio     1.2:1:1 - 1.5:1       Projection distance (m)     1.2:1:1 - 1.5:1       Connectivity     Units: 2:x HDMI 2.0; 3:x USB-A, 1:x HDMI 2.0 (sARC)       Outputs 1:x Audio 3:5mm, 1:x SPDIF     Control 1: X RS22, 1:x RU45, 1:x 12V trigger, 1:x 3D sync       General     Noise level (max)     2:3:d       Noise level (max)     2:3:d     SAMME2, 4:3:MHE, 4:3:MHE, 4:3:MHE, 4:3:MHE, 5:d       2D compatibility     UHD, FHD, UKGA, SKGA, WXGA, HD, XGA, SVGA, VGA, Mac       2D compatibili	Brightness	3,000 lumens
Aspect ratio - compatible     4:3       Keystone correction - vertical     +/-40°       Heas vertical auto keystone     Yes       Correction     Displayable colours (millions)     1073.4       Morizontal scan rate     50-120k-brkz       Uniformity     80%       Screen size     0.26m - 7.68m (34.1" - 302.4") diagonal       Lamp Info     Laser       LASER life     30.000 hours       Optical     1.21:1 - 1.59:1       Projection distance (m)     1.2:1:1 - 1.59:1       Projection distance (m)     1.2:1:1 - 1.59:1       Zoom type     Manual       Focal length (mm)     1.2:1:1 - 1.59:1       Control     1.3       Zoom type     Manual       Focal length (mm)     1.2:1:1 - 1.59:1       Projection distance (m)     1.2:1:1 - 1.59:1       Control tistance (m)     1.2:1:1 - 1.59:1       Control tistance (maint)     1.2:1:1 - 1.59:1       Projection distance (m)     1.2:1:1 - 1.59:1       Connections     Inputs 2 x HDMi 2.0; 3 x USEr.A, 1 x HDM 2.0 (eAPC)       Outputs 1 x Audio 3:5mm, 1 x SUPDIE     Connections       Outputs 1 x Audio 3:5mm, 1 x SUPDIE     Control 1 x RS23, 1 x RJ45, 1 x 12V tigger, 1 x 3D sync       General     Noise level (max)     2:5dB       Ocospatibility     UHD, FHD, UXGA, SVGA, WXGA, HD, XGA, SVG		2,500,000:1
Keystone correction - +/-40° harizontal Keystone correction - vertical +/-40° Has vertical auto keystone correction = 15.575 - 91.146 khr. Vertical scan rate = 50 - 12044/rz Uniformity = 80% Sereen size = 0.87m - 7.68m (34.1° - 302.4″) diagonal Lamp Info Light source type = Laser LASER life = 30,000 hours Optical Throw ratio = 1.211 - 1.59:1 Projection distance (m) = 2.5120(2000 - 0.0000 / 0	Native aspect ratio	16:9
horizontal Krystone correction - vertical severical auto keystone correction Diplayable colours (millions) 1073.4 Horizontal scan rate 50 - 120kt-ktz Uniformity 80% Screen size Darm - 7.68m (34.1" - 302.4") diagonal Lamp Info Light source type Laser LASER life 30,000 hours Optical Throw ratio Projection distance (m) 1.21:1 - 1.50:1 Projection distance (m) 2.01:1 - 1.50:1 Projection distance (m) 2.01:1 - 1.50:1 Projection distance (m) 2.01:1 - 1.50:1 Projection distance (m) 2.01:1 - 1.50:1 Projection distance (m) 2.01:1 -	Aspect ratio - compatible	4:3
Keystone correction - vertical     +/-40°       Has vertical auto keystone     Yes       Orightyable colours (millions)     1073.4       Horizontal scan rate     55.375 - 91.148 Khz       Vertical scan rate     50 - 120/4b/z       Uniformity     80%       Screen size     0.87m - 7.68m (34.1* - 302.4*) diagonal       Lamp info     Laser       LASER life     30,000 hours       Optical     7       Throw ratio     1.21:1 - 1.59:1       Projection distance (m)     1.21:1 - 1.54.1       Conn     1.3       Zoom type     Manual       Focal length (mm)     1.22:1 - 3.1m       Zoom type     Manual       Focal length (mm)     1.25.41mm-16.74mm       Lens shift     Vertical + 10%       Native offset     105%       Connectivity     Control 1 x R522.1 x RU45.1 x 12V trigger, 1 x 3D sync       Connectivity     27dB       Noise level (max)     23dB       PC compatibility     UHD, HD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       20 compatibility     UHD, HD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       21 compatibility     SccCAM ED/G/A/XIT, 4.25/4 Malke 240/0, 57/0, 720,06/00-Hz, 1080,02/4, 720,05/0 60       30     Funits, Fertch, Gamma, Graek, Hungaran, Indonesai, Talak, Japanese, Norweglan, Polik, Parly, Parly, 720,05/060-H2, 720,05/06		+/-40°
He vertical auto keystone Ves correction Diplayable colours (millions) 1073.4 Horizontal scan rate 15.375 – 91.146 Khz Vertical scan rate 00 – 120HzHz Uniformity 80% Screen size 0.87m – 7.88m (34.1* – 302.4*) diagonal Lamp info Light source type Laser Light source type Laser Light source type 10.000 hours Optical Throw ratio 1.21:1 – 1.59:1 Projection distance (m) 1.22:1 m m Lens shift Verical + 1.05% Lens shift Verical + 1.05% Lons shift Verical + 1.05% Lons shift Verical + 1.05% Lons shift Verical + 1.05% Lens shift Verical + 1.05% Lens shift Verical + 1.05% Lons shift Verical + 1.05% Lens shift Veric		4.400
correction     1073.4       Displayable colours (millions)     1073.4       Horizontal scan rate     15.375 - 91.146 KHz       Vertical scan rate     50 - 120HzHz       Uniformity     80%       Screen size     0.87m - 7.68m (34.1* - 302.4*) diagonal       Lamp info     Laser       Laff source type     Laser       LASER life     30,000 hours       Optical     Throw ratio       Throw ratio     1.21:1 - 1.59:1       Projection distance (m)     1.2       Zoom     1.3       Zoon type     Manual       Focal length (mm)     1.2.8.1       Lens shift     Vertical +10%       Native offset     105%       Connections     Inputs 2.x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)       Outputs 1 x Audio S.5mm, 1 x S/PDIF     Control 1 x R5232, 1 x PU46, 1 x 12V trigger, 1 x 3D sync       General     Noise level (max)       20 compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       20 compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       20 compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       20 compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       20 compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, 2006, 760, 770, 5760, 770, 50760, 770, 770, 5760, 770, 770, 5760, 770, 770, 5760, 770,		
Displayable colours (millions)     1073.4       Horizontal scan rate     15.375 - 91.146 Khz       Workical scan rate     50 - 120H2Hz       Uniformity     80%       Screen size     0.87m - 7.88m (34.1* - 302.4*) diagonal       Lamp info     Light source type       Light source type     Laser       LASER life     30.000 hours       Optical     1.21:1 - 1.50:1       Throw ratio     1.21:1 - 1.50:1       Projection distance (m)     1.2m - 8.1m       Zoom type     Manual       Focal length (mm)     1.2.81mm -16.74mm       Lens shift     Verical +10%       Native offset     105%       Lens shift     Verical +10%       Connectivity     Inputs 2 x HDM12.0, 3 x USB-A, 1 x HDM12.0 (eARC)       Outputs 1 x Audio 3.5mm, 1 x S/PDIF     Control 1 x R5232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync       General     Vise level (max)       PC compatibility     UHD, FHD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     Side-108050 / 60, 720,50 / 60 Fam-pack: 1080/50/60, 720,50 / 60 Fam-pack: 1080/52/4, 720,50 / 60 Fam-packe, 1080/4, 104/54, 1080/60/64/1, 1080/60/64/1, 1080/60/64/1, 1080		Yes
Horizontal scan rate 15.375 – 91.146 Khz Vartical scan rate 50 – 120HzHz Uniformity 80% Screen size 0.87m – 7.68m (34.1* – 302.4*) diagonal Lamp info Later 1.000 (1.1 – 1.59:1 Projection distance (m) 1.21:1 – 1.59:1 Prower ensumption (m) 1.75:W Prower consumption (m) 1.75:W		1073 /
Vertical scan rate     50 - 120H2H2;       Uniformity     80%       Screen size     0.87m - 7.68m (24.1* - 302.4*) diagonal       Lamp info     Laser       LASER life     30,000 hours       Optical     Throw ratio       Throw ratio     1.21:1 - 1.59:1       Projection distance (m)     1.21:1 - 1.59:1       Zoom type     Manual       Focal length (mm)     1.2.81m.       Lens shift     Vertical + 10%       Native offset     105%       Connections     Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (sARC)       Outputs 1 x Audio 3.5mm, 1 x S/PDIF     Connections       Connections     Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (sARC)       Outputs 1 x Audio 3.5mm, 1 x S/PDIF     Connections       Connections     UHD, FHD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       PC compatibility     UHD, FHD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       PC compatibility     UHD, FHD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     Steleward (max)       2D compatibility     UHD, FHD, UXGA, SXGA, WGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     Steleward (max)       2D compatibility     Steleward (max)       2D compatibility     Steleward (max)       2D compatibility     Steleward (max), Reshift, Chapata, Indona, Russia, Chapata, Indona, Russia,		
Uniformity         80%           Screen size         0.87m - 7.68m (34.1" - 302.4") diagonal           Lamp info         Laser           LASER life         30000 hours           Optical         Trow ratio         1.21:1 - 1.59:1           Projection distance (m)         1.21:1 - 1.59:1           Projection distance (m)         1.21:1 - 1.59:1           Scom         1.3           Zoom type         Manual           Focal length (mn)         12.81mm - 16.74mm           Lens shift         Vertical + 10%           Native offset         105%           Lens shift         Vertical + 10%           Native offset         105%           Connectivity         Outputs 1 x Audio 3.8mm, 1 x S/PDIF           Connections         Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)           Outputs 1 x Audio 3.8mm, 1 x S/PDIF         Control 1 x R5232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync           General         Scompatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         UHD, CHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, YGA, Mac           2D compatibility         Stab-by-Stab (2006/06/12, 1200/06/06/12, 1200/06/06/12, 1200/06/06/12, 1200/06/06/12, 1200/06/06/12, 1080/06/06/12, 1080/06/06/12, 1080/06/06/12, 1080/06/06/12, 1080/06/06/12, 1080/06/06/12, 1080/06/06/12, 1080/06/06/12, 108		
Sereen size         0.87m ~ 7.68m (34.1" ~ 302.4") diagonal           Lamp info         Laser           LASER life         30,000 hours           Optical         Throw ratio           Throw ratio         1.21:1 ~ 1.59:1           Projection distance (m)         1.2m ~ 8.1m           Zoom         1.3           Zoom type         Manual           Focal length (mm)         12.81mm-16.74mm           Lens shift         Vertical + 10%           Native offset         105%           Connections         Inputs 2 x HDMI 2.0, 3 x USE-A, 1 x HDMI 2.0 (eARC)           Outputs 1 x Audio 3.6mm, 1 x S/PDIF         Control 1 x R5232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync           General         Noise level (max)           Noise level (max)         26dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           20 compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           21 compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           20 compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           21 compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           20 compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           21 compa		
Lamp info         Laser           LaSER life         30,000 hours           Optical         Throw ratio         1.21:1 ~ 1.59:1           Projection distance (m)         1.2m - 8.1m           Zoom ype         Manual           Focal length (nm)         12.81mm-16.74mm           Lens shift         Verical +10%           Native offset         105%           Lens shift         Verical +10%           Connectivity         Connectivity           Connectivity         Connectivity           Connectivity         22dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           Doise level (max)         28dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           20 compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           20 compatibility         Side by-Side:108050 / 60, 720;50 / 60           3D         Full SD           Security         Security bar, Kensington Lock, Password protected interface           0SD / display languages         25 languages: Adplic, 2ach, Jamish, Dutch, Fulsh, Farate, 2B languages: Nonvegian, Polish, Portuguese, Romanian, Russian, Chinese (interface           0SD / display languages         0'C -40''C/1'F - 104''F, max altitude 3000/W9843ft, max humidity 55''s		
Light source type LASER life 30,000 hours  Optical  Throw ratio 1,21:1 – 1.59:1  Projection distance (m) 1,2m - 8.1m  Zoom 1,3  Zoom type Manual  Focal length (mm) 12.81mm - 16.74mm Lens shift Verical + 10% Native offset 105% Lens shift Verical + 10% Connectivity Connectivity Connections Inputs 2 x HDMI 2.0, 3 x USE-A, 1 x HDMI 2.0 (aARC) Outputs 1 x Audio 3.5mm, 1 x SPDIF Compatibility Proceeding 2 x HDMI 2.0, 3 x USE-A, 1 x HDMI 2.0 (aARC) Outputs 1 x Audio 3.5mm, 1 x SPDIF Connectivity Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync Control 1 x RS232, 1 x RJ45, 1 x 12V trigger		olorini Filodin (om objecti ) didgondi
LASER life     30,000 hours       Optical     Throw ratio       Projection distance (m)     1.2m - 8.1m       Zoom     1.3       Zoom type     Manual       Focal length (mm)     12.81mm-16.74mm       Lens shift     Vertical + 10%       Native offset     105%       Connectivity     Connectivity       Connectivity     Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)       Outputs 1 x Audio 3.6mm, 1 x S/PDIF     Connectivity       Connectivity     UPD. FHD, UKGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       PC compatibility     UPD. FHD, UKGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       PC compatibility     UPD. FHD, UKGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     URD. FHD, UKGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     UBO,P24, 720,P50 / 60, Frame-pack:       3D compatibility     Side-by-Side:108,050 / 60, 720,P50 / 60       3D     Full 3D       Security     Security bar, Knaington Lock, Password protected interface       CSD / display languages     Chicese (amplified), Spanish, Duch, English, Farsi, Fransi, Fransi, Fransi, Fransi, Fransi, Ganaish, Cach, Danish, Duch, English, Farsi, Fransi, Fransi, Vetramese       24/7 operation     Yes       Operating conditions     O'C -40°/C/1*F-104*F, max altitude 3000M/9843t, max humality E35% from the box       Power cord     Remote contr		Laser
Optical         1.21:1 - 1.59:1           Throw ratio         1.27: - 8.1m           Zoom         1.3           Zoom type         Manual           Focal length (mm)         12.81:mm - 16.74:mm           Lens shift         Vertical + 10%           Native offset         105%           Lens shift         Vertical + 10%           Connectivity         Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)           Outputs 1 x Audio 3.5mm, 1 x S/PDIF         Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync           General         29dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           Doise level (max)         29dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           3D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           3D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           3D compatibility         Side-bw-Side:108060 /60/H2, 1080/G0/60/H2, 1080/G		
Throw ratio       1.21:1 = 1.59:1         Projection distance (m)       1.2m - 8.1m         Zoom       1.3         Zoom type       Manual         Focal length (mm)       12.81mm - 16.74mm         Lens shift       Verical + 10%         Native offset       105%         Connectivity       Connectivity         Connectivity       Connectivity         Connectivity       Connectivity         Connectivity       Connectivity         Connectivity       Connectivity         Connectivity       Connectivity         Connectivity       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         20 compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         20 compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         20 compatibility       Side-by-Side:1080i50 / 60, 720;050 / 60 Fame-pack:         20 compatibility       Side-by-Side:1080i50 / 60, 720;050 / 60 Fame-pack:         30 compatibility       Side-by-Side:1080i50 / 60, 720;050 / 60 Fame-pack:         30 compatibility       Side-by-Side:1080i50 / 60, 720;050 / 60 Fame-pack:         30 compatibility       Side-by-Side:1080i50 / 60, 720;050 / 60 Fame-pack:         30 compatibility       Side-by-Side:1080i50 / 60, 720;050 / 60 Fame-pack:		
Projection distance (m)       1.2m - 8.1m         Zoom       1.3         Zoom type       Manual         Focal length (mm)       12.81mm - 16.74mm         Lens shift       Verical +10%         Native offset       105%         Lens shift       Verical +10%         Connectivity       Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)         Outputs 1 x Audio 3.5mm, 1 x Si/PDIF       Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync         General       20dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, MA         2D compatibility       VHTSC MU, 35MHz, 4 x3MHz PAL B/O/G/H/UMMN, 4,43MHz         SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576//p, 720(60/00Hz)       1080p/24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 6	-	1.21:1 ~ 1.59:1
Zoom     1.3       Zoom type     Manual       Focal length (mm)     12.81mm-16.74mm       Lens shift     Vartical +10%       Native offset     105%       Lens shift     Yes - ([downloads_link])       Connectivity     Connectivity       Connectivity     Outputs 1 x Audio 3.5mm, 1 x S/PDIF       Connectivity     Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync       General     29dB       PC compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac       2D compatibility     VTSC KMJ, 3.58MHz, 4.43MHz PAL BD/02/HUMM, 4.43MHz       2D compatibility     SECAM BD/02/K/K1, 4.25/4.44MHz 480/p, 576//p, 720p50/60Hz), 1080(p60Hz), 1080(p20Hz), 1080(p20Hz), 1080(p60Hz), 1080(p60Hz), 1080(p20Hz), 1080(p60Hz), 1080(p20Hz), 1080(p20Hz		
Focal length (mm)       12.81mm-16.74mm         Lens shift       Verical +10%         Native offset       105%         Lens shift       Yes - {{downloads_link}}         Connectivity       Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)         Outputs 1 x Audio 3.5mm, 1 x S/PDIF       Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync         General       29dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         3D compatibility       Scourby         3D compatibility       Side-by-Side: 1080050 / 60, 72050 / 60 Frame-pack:         1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60       Scourby         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F- 104°F, max altitude 3000M/9843ft,	Zoom	1.3
Focal length (mm)       12.81mm-16.74mm         Lens shift       Verical +10%         Native offset       105%         Lens shift       Yes - {{downloads_link}}         Connectivity       Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)         Outputs 1 x Audio 3.5mm, 1 x S/PDIF       Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync         General       29dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         3D compatibility       Scourby         3D compatibility       Side-by-Side: 1080050 / 60, 72050 / 60 Frame-pack:         1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60       Scourby         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F- 104°F, max altitude 3000M/9843ft,	Zoom type	Manual
Lens shift       Vertical +10%         Native offset       105%         Lens shift       Yes - ([downloads_link])         Connections       Inputs 2 × HDMI 2.0, 3 × USB-A, 1 × HDMI 2.0 (eARC)         Outputs 1 × Audio 3.5mm, 1 × S/PDIF       Control 1 × RS232, 1 × RJ45, 1 × 12V trigger, 1 × 3D sync         General       27dB         Noise level (typical)       27dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, Mac         2D compatibility       Side-by/S(XK1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz), 108	Focal length (mm)	12.81mm~16.74mm
Lens shift         Yes - {{downloads_link}}           Connectivity Connections         Inputs 2 × HDMI 2.0, 3 × USB-A, 1 × HDMI 2.0 (eARC)           Outputs 1 × Audio 3.5mm, 1 × S/PDF Control 1 × RS232, 1 × RJ45, 1 × 12V trigger, 1 × 3D sync           General Noise level (typical)         27dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         SecAm B/D/G/K/K1/L, 4.25/4.4MHz PAL B/D/G/H/U/M/N, 4,43MHz           3D compatibility         Side-by-Side:108050 / 60, 720p50 / 60 Frame-pack:           1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60         Space           3D         Full 3D           Security         Security bar, Kensington Lock, Password protected interface           OSD / display languages         25 languages: Arabic, Czen, Danish, Durch, Lenglish, Faris, Finnish, Farch, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vetnamese           24/7 operation         Yes           Operating conditions         9(°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85%           <		Vertical +10%
Connectivity Connections         Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)           Outputs 1 x Audio 3.5mm, 1 x S/PDIF Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync           General Noise level (typical)         27dB           Noise level (max)         29dB           PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           2D compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac           3D compatibility         Side-by-Side:108005 /60.12, 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz)           3D compatibility         Side-by-Side:1080(50 /60.720, 50 /60.720, 56 //p, 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 576 //p, 720p(50/60 / 60.720, 50 / 60           3D         Full 3D           Security         Security bar, Kensington Lock, Password protected interface           OSD / display languages         25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norweglan, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese           24/7 operation         Yes           Operating conditions         0°C-40°C/41°F-104°F, max atitude 3000M/9843ft, max humidity 85%           Remote control         Backlit home remote           Heat dissipation         918BTU/hour           Speaker count         2	Native offset	105%
Connections       Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)         Outputs 1 x Audio 3.5mm, 1 x S/PDIF         Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync         General         Noise level (typical)         Noise level (max)         29dB         PC compatibility         UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility         D'Compatibility         3D compatibility         Security	Lens shift	Yes - {{downloads_link}}
Outputs 1 x Aulois 0, Simu, 1 x SPDIF         Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync         General         Noise level (typical)       27dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         3D security       Side-by-Side:1080150 / 60, 720p50 / 60 Frame-pack:         3D security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C-40°C/41°F-104°F, max attitude 3000M/9843ft, max humidity 85%         Remote control       BackIt home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W	Connectivity	
Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync         General       Yinter Strength         Noise level (typical)       27dB         Noise level (max)       29dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       Side-by-Side:1080150 / 60, 720,50 / 60 Frame-pack:         3D compatibility       Side-by-Side:1080150 / 60, 720,50 / 60 Frame-pack:         3D compatibility       Security bar, Kensington Lock, Password protected interface         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F- 104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control in CR2025 battery       Quick star	Connections	Inputs 2 x HDMI 2.0, 3 x USB-A, 1 x HDMI 2.0 (eARC)
General       27dB         Noise level (typical)       27dB         Noise level (max)       29dB         PC compatibility       UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac         2D compatibility       NTSC KMJ, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz         2D compatibility       SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p50/60Hz)         3D compatibility       Side-by-Side:1080150/60Hz, 108006/00Hz)         3D compatibility       Side-by-Side:1080150/60 / 60, 720p50 / 60         3D       Full 3D         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control in CR2025 battery       Quick start user manual USB wireless adapter         Input		Outputs 1 x Audio 3.5mm, 1 x S/PDIF
Noise level (typical)27dBNoise level (max)29dBPC compatibilityUHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac2D compatibilityNTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz2D compatibilitySECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz)3D compatibilitySide-by-Side:1080(50/60Hz), 1080p(50/60Hz)3D compatibilitySecurity 20p(50/60Hz), 1080(50/60Hz), 1080p24, 720p50 / 603DFull 3DSecuritySecurity bar, Kensington Lock, Password protected interfaceOSD / display languages25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese24/7 operationYesOperating conditions0°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85%Remote controlBacklit home remoteHeat dissipation918BTU/hourSpeaker count2Watts per speaker10WIn the boxAC power cord Remote control inc CR2025 battery Ouick start user manual USB wireless adapterInput lag400V – 240V, 50-60HzPower consumption (standby)<0.5WPower consumption (max)230WWeight and dimensions Dimensions (W x D x H) mm337 x 265 x 122.5Gross weight6.5 kg		Control 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x 3D sync
Noise level (max)29dBPC compatibilityUHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac2D compatibilityNTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/M/N, 4.43MHz2D compatibilitySECAM B/D/G/K/K/1/L, 4.254/4.MHz 480(r), 576(r), 720p(50/60Hz), 1080(50/60Hz), 1080(50/60Hz)3D compatibilitySide-by-Side:1080(50/60 Ve0, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 603DSecuritySecurity bar, Kensington Lock, Password protected interfaceOSD / display languages25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese24/7 operationYesOperating conditions0°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85%Remote controlBacklit home remoteHeat dissipation918BTU/hourSpaker count2Watts per speaker10WIn the boxAC power cord Remote control inc CR2025 battery Ouick start user manual USB wireless adapterInput lag400msPower consumption (min)175WPower consumption (min)175WPower consumption (max)230WWeight and dimensions Dimensions (W x D x H) mm337 x 265 x 122.5Gross weight6.5 kg		
PC compatibility     UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, VGA, Mac       2D compatibility     NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz       2D compatibility     SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480/p, 576/p, 720p(50/60Hz), 1080(50/60Hz)       3D compatibility     Side-by-Side:1080150 / 60 Prame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60       3D     Security bar, Kensington Lock, Password protected interface       OSD / display languages     25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (ismplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese       24/7 operation     Yes       Operating conditions     0°C - 40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%       Remote control     Backlit home remote       Heat dissipation     918BTU/hour       Speaker count     2       Watts per speaker     10W       In the box     AC power cord Remote control in CR2025 battery Quick start user manual USB wireless adapter       Input lag     4.00ms       Power     2400 - 240V, 50-60Hz       Power consumption (standby)     -0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg		
2D compatibility       NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz         SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480(/p, 576(/p, 720p50/60Hz), 1080(50/60Hz), 1080(50/60Hz), 1080p(50/60Hz)         3D compatibility       Side-by-Side:1080(50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60         3D       Full 3D         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C-40°C/41°F-104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Power       Power         Power consumption (standby)       <0.5W         Power consumption (max)       20W         Weight and dimensions       20W         Dimensions (W x D x H) mm       337 x 265 x 122.5         Gross weight       6.5 kg	. ,	
SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080)(50/60Hz), 1080p(50/60Hz)3D compatibilitySide-by-Side:1080)50 / 60, 720p50 / 603DFull 3DSecuritySecurity bar, Kensington Lock, Password protected interfaceOSD / display languages25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese24/7 operationYesOperating conditions0°C-40°C/41°F-104°F, max attitude 3000M/9843ft, max humidity 85%Remote controlBacklit home remoteHeat dissipation918BTU/hourSpeaker count2Watts per speaker10WIn the boxAC power cord Remote control in CR2025 battery Ouick start user manual USB wireless adapterInput lag4.00msPower90wer consumption (standby)Power consumption (standby)<0.5WPower consumption (max)230WWeight and dimensions Dimensions (W x D x H) mm337 x 265 x 122.5Gross weight6.5 kg		
1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60         3D       Full 3D         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F - 104°F, max attitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control in the box       AC power cond         Input lag       4.00ms         Power       90Wer         Power consumption (standby)       <0.5W         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg	2D compatibility	SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,
3D       Full 3D         Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F - 104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control in CR2025 battery       Quick start user manual         USB wireless adapter       100V ~ 240V, 50-60Hz         Power consumption (standby)       <0.5W         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg	3D compatibility	
Security       Security bar, Kensington Lock, Password protected interface         OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,         Finnish, French, German, Greek, Hungarian, Indonesian, Italian,       Japanese, Norwegian, Polish, Portuguese, Romanian, Russian,         Chinese (implified), Spanish, Swedish, Chinese (traditional),       Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C - 40°C/41°F - 104°F, max altitude 3000M/9843ft, max         humidity 85%       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control inter (CR2025 battery)       Quick start user manual         USB wireless adapter       100V - 240V, 50-60Hz         Power       20.5W         Power consumption (standby)       <0.5W         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg		
OSD / display languages       25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (itaditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord Remote control inc CR2025 battery Quick start user manual USB wireless adapter         Input lag       4.00ms         Power       100V ~ 240V, 50-60Hz         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg		
Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese         24/7 operation       Yes         Operating conditions       0°C-40°C/41°F104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control in the box       AC power cord         Nerver       2000 × 240V, 50-60Hz         Power       100V ~ 240V, 50-60Hz         Power consumption (standby)       <0.5W         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg		
Operating conditions       0°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control inc CR2025 battery       Quick start user manual         USB wireless adapter       USB wireless adapter         Input lag       4.00ms         Power       00V ~ 240V, 50-60Hz         Power consumption (standby)       <0.5W         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg	OSD / display languages	Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),
humidity 85%         Remote control       Backlit home remote         Heat dissipation       918BTU/hour         Speaker count       2         Watts per speaker       10W         In the box       AC power cord         Remote control inc CR2025 battery       Quick start user manual         USB wireless adapter       USB wireless adapter         Input lag       4.00ms         Power       Power consumption (standby)         Power consumption (min)       175W         Power consumption (max)       230W         Weight and dimensions       337 x 265 x 122.5         Gross weight       6.5 kg	24/7 operation	
Heat dissipation918BTU/hourSpeaker count2Watts per speaker10WIn the boxAC power cord Remote control inc CR2025 battery Quick start user manual USB wireless adapterInput lag4.00msPower100V ~ 240V, 50-60HzPower consumption (standby)<0.5WPower consumption (max)230WWeight and dimensions337 x 265 x 122.5Gross weight6.5 kg		humidity 85%
Speaker count     2       Watts per speaker     10W       In the box     AC power cord Remote control inc CR2025 battery Quick start user manual USB wireless adapter       Input lag     4.00ms       Power     100V ~ 240V, 50-60Hz       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg		
Watts per speaker     10W       In the box     AC power cord       Remote control inc CR2025 battery     Quick start user manual       USB wireless adapter     USB wireless adapter       Input lag     4.00ms       Power     100V ~ 240V, 50-60Hz       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg		
In the box     AC power cord Remote control inc CR2025 battery Quick start user manual USB wireless adapter       Input lag     4.00ms       Power     00V ~ 240V, 50-60Hz       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg		
Remote control inc CR2025 battery Quick start user manual USB wireless adapter       Input lag     4.00ms       Power     7       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg		
Ouick start user manual USB wireless adapter       Input lag     4.00ms       Power     100V ~ 240V, 50-60Hz       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg	III UIE DOX	
USB wireless adapter           Input lag         4.00ms           Power         100V ~ 240V, 50-60Hz           Power consumption (standby)         <0.5W           Power consumption (min)         175W           Power consumption (max)         230W           Weight and dimensions         337 x 265 x 122.5           Gross weight         6.5 kg		
Power     100V ~ 240V, 50-60Hz       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg		USB wireless adapter
Power supply     100V ~ 240V, 50-60Hz       Power consumption (standby)     <0.5W       Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Gross weight     6.5 kg	Input lag	4.00ms
Power consumption (standby)     <0.5W		
Power consumption (min)     175W       Power consumption (max)     230W       Weight and dimensions     337 x 265 x 122.5       Dimensions (W x D x H) mm     337 x 265 x 122.5       Gross weight     6.5 kg		
Power consumption (max)         230W           Weight and dimensions		
Weight and dimensions       Dimensions (W x D x H) mm     337 x 265 x 122.5       Gross weight     6.5 kg		
Dimensions (W x D x H) mm         337 x 265 x 122.5           Gross weight         6.5 kg		230W
Gross weight 6.5 kg	-	
•		
Net weight 4.8 kg	, and the second s	5
	ivet weight	4.8 Kg







Copyright © 2021, Optoma and its logo is a registered trademark of Optoma Corporation. Optoma Europe Ltd is the licensee of the registered trademark. All other product names and company names used herein are for identification purposes only and may be trademarks or registered trademarks of their respective owners. Errors and omissions excepted, all specifications are subject to change without notice. All images are for representation purposes only and may be simulated. 11112021093807