

- “Designed for touch” with proven Elo expertise and reliability
- A bright, high-contrast display with wide viewing angle easily attracts and holds the user’s attention
- 3 year warranty



2239L 22” Open-Frame Wide-Aspect LCD Touchmonitor

Elo Touch Solutions open-frame touchmonitor series features the 2239L that delivers a cost-effective touch solution for OEMs and systems integrators, and complements Elo's expanded family of touch solutions for gaming and amusement, retail self-service and kiosk applications. This compact 3000-series touchmonitor is “designed for touch”, with Elo's proven expertise and reliability built-in, not added as an afterthought by altering an existing monitor.

The 2239L features a brilliant wide-viewing-angle LCD panel to instantly grab and hold the user's attention, whether they are checking out retail goods with a self-service kiosk or playing games in a casino or arcade. Because the enclosure is controlled by Elo's specifications and tooling, Elo's openframe monitors have a long-lasting product cycle, which is important to maintain continuity through all phases of project rollouts and servicing. The 2239L uses clear-glass IntelliTouch surface-

wave technology to deliver optical quality, durability, and drift-free stability. It also features a unique, injection-molded bezel with a virtually invisible watertight seal, making it a good choice for the rigors of public use. Narrow borders, multiple mounting options, and a dual serial/USB touch interface add to the versatility of the 2239L. Worldwide agency approvals, as outlined on the back side of this sheet, cover the entire monitor that is designed, built and supported by Elo Touch Solutions, a true single-source supplier.

The 2239L is available with a choice of the innovative IntelliTouch surface acoustic wave, and surface-capacitive touch technologies. The comprehensive range of features includes analog and digital interfaces, multi-lingual on-screen display (OSD), mounting VESA standard, mounting brackets, cabled remote on-screen display (OSD), and worldwide compliance.



Benefits:

- Elo Touch Solutions IntelliTouch (surface acoustic wave) technology offers high-quality optics, durability, and long-term reliability
- A transparent protective coating makes the touchscreen resistant to scratches and abrasions
- A sealed bezel that resists liquid splashes and spills adds additional protection to the touchmonitor
- The enclosure is controlled by Elo Touch Solutions specifications and results in a long-lasting product cycle.
- Multiple mounting options are available.
- Dual serial and USB connectivity are standard.

Application:

- Casino and amusement games
- Retail self-service
- Kiosks

About Elo

Elo founders pioneered the touch screen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

2239L 22" Open-Frame Wide-Aspect LCD Touchmonitor

Case/Bezel Color	Dark gray
Display Type	Active matrix TFT LCD
Display Size	22.0" diagonal
Useful Screen Area	Horizontal: 473.8 mm Vertical: 296.1 mm
Monitor Dimensions	Width: 530 mm Height: 352 mm Depth: 78 mm
Optimal (Pre-Set) Resolution	1680 x 1050 @ 60 Hz (90 pixels/inch)
Other Supported Resolutions	640 x 480 @ 60 Hz, 640 x 480 @ 66 Hz, 640 x 480 @ 72 Hz, 720 x 350 @ 70 Hz, 720 x 400 @ 70 Hz, 800 x 500 @ 75 Hz, 800 x 600 @ 56 Hz, 800 x 600 @ 60 Hz, 800 x 600 @ 72Hz, 832 x 624 @ 75 Hz, 1024 x 768 @ 60 Hz, 1024 x 768 @ 65 Hz, 1024 x 768 @ 72Hz, 1024 x 768 @ 75 Hz, 1152 x 864 @ 75 Hz, 1280 x 960 @ 60 Hz, 1280 x 1024 @ 60 Hz, 1280 x 768 @ 65 Hz, 1280 x 1024 @ 75 Hz, 1360 x 768 @ 60 Hz, 1366 x 768 @ 60 Hz; 1600 x 1200 @ 60 Hz, 1680 x 1050 @ 75 Hz
Colors	16.7 million colors
Brightness (typical)	LCD Panel: 300 cd/m ² , min. 250 cd/m ² with IntelliTouch: 270 cd/m ² , min. 212 cd/m ²
Response Time	Typical Rise Time 5 msec; Typical Fall Time 5 msec
Viewing Angle (typical)	Horizontal: 170° at a CR>10 Vertical: 160° at a CR>10
Contrast Ratio	1000:1 (typical)
Input Video Format	1. RGB Analog Video 2. DVI Video (not available on 2239L-xxx-x-A-x) models
Input Sync Format	Separate H & V sync, Composite Sync, and Sync-On-Green
Input Video Signal Connector	1. 15-pin female D-sub for Analog Video 2. Female DVI-D for Digital Video
Scanning Frequency Ranges	Horizontal: 30 - 75 kHz Vertical: 56 - 75 Hz
Power Consumption	50W typical, 75W maximum (at 120V/60Hz input)
Power Supply - Internal	Monitor Input Voltage: 100~240 VAC, 50/60Hz
Temperature	Operating: 0°C to 40°C Storage: -20°C to 60°C
Humidity	Operating: 20% to 80% humidity (non-condensing) Storage: 10% to 90% humidity (non-condensing)
Monitor MTBF (excluding lamps)	50,000 hours demonstrated
Backlight Lamp Life	50,000 hours (typical); 40,000 minimum
Weight (approx.)	Actual: 8.48 kg; Shipping: 12.59 kg
Other Features	100 mm VESA mount; Digital on-screen display (OSD); User's control: OSD buttons: menu, up, down, select; OSD: automatic adjustment, contrast, brightness, H/V position, clock, phase, color temperature, input video select, OSD H/V position, OSD timeout, language (English, French, Italian, German, Spanish, Japanese, Traditional Chinese, Simplified Chinese), recall color, recall defaults, sharpness, display information; OSD locking/unlocking and power locking/unlocking
Warranty	TouchMonitor: 3 years
Touch Interface	USB and Serial (IntelliTouch)
Agency Certification	UL (US), cUL (Canada), GS Mark (Germany), FCC (US), CE (EU), NOM (Mexico), PCT (Russia), CCC/RoHS (China), eK/Mic (Korea), BSMI (Taiwan), Singapore, VCCI (Japan), C-Tick (Australia) and S-mark (Argentina), WEEE, IMERC.

Ordering Information

Model	Part Number	Technology	Interface	Surface Treatment	Availability
2239L	E654071	IntelliTouch	Dual serial/USB	Antiglare	Americas
	E230376	IntelliTouch	Dual Serial/USB	Clear	Americas
	E523763	IntelliTouch	Dual serial/USB	Clear	Asia/Pacific
	E629432	IntelliTouch	Dual serial/USB	Antiglare	Asia/Pacific
	E807682	IntelliTouch	Dual serial/USB	Antiglare	EMEA
	E846997	IntelliTouch	Dual serial/USB	Clear	EMEA

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8001
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel 786-923-0251
Fax 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. Copyright 2014 Elo Touch Solutions, Inc. All rights reserved. DS000027, rev A 03/14

