ThinkCentre M75q Tiny 11A4000FBL

Product

ThinkCentre M75q-1 Tiny

Region

EET

Country/Region

Bulgaria

Machine Type

11A4

TopSeller

TopSeller

Processor

AMD Ryzen 5 PRO 3400GE (4C / 8T, 3.3 / 4.0GHz, 2MB L2 / 4MB L3)

Chipset

AMD B300 Chipset

Graphics

Integrated AMD Radeon Vega 11 Graphics

Memory

1x 8GB DDR4-2666

Storage

256GB SSD M.2 2280 PCIe x4 NVMe opal

Optical

None

Speaker

1.5Wx1

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

RTL8822CE 11ac. 2x2 + BT5.0

Optional Rear Ports

None

Chassis Intrusion Switch

Chassis Intrusion Switch

Kensington Cable Lock

None

Adapter Cage

Adapter Cage

Toolless Chassis Screw

Toolless Chassis Screw

Dust Filter

None

VESA Mount

VESA Mount

Color

Black

Stand

None

Keyboard

USB Traditional Keyboard, Black, Bulgarian

Mouse

USB Calliope Mouse

Power Supply

65W 88% Adapter

TUV Low Noise

None

Monitor Cable

None

System Management

DASH

Operating System

Windows 10 Pro 64, English

Bundled Software

None

Base Warranty

3-year, Onsite

Bundled Service

None

EAN/UPC/JAN

0194552486082

End of Support

2025-11-15

Announce Date

2019-10-15

Recommended Services

Pottor

4Y Premier Support Upgrade from 3Y Onsite (5WS0T36207)

Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26647)

L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2020. All rights reserved.



ThinkCentre M75q-1 Tiny Platform Specifications

Athlon Athlon Ryzen 3 Ryzen 5 Ryzen S Ryzen S	on PRO 200GE on PRO 300GE 3 PRO 2200GE 5 PRO 2400GE 5 PRO 3400GE 5 PRO 3400GE 5 PRO 3400GE max, DDR4-26 mb board support 1866, DDR4-213 : Hard Drive / : M.2 SSD (22 : DVD-ROM, 9 : DVD±RW, 9 : ATA 6.0Gb/s c Radeon™ Gra yPort™, one H pendent displa using HDMI pc rt 2 displays) esolution: 4096 1920	666*, tw ts up to E 33 or DDI SATA 6. 242 / 226 9.0mm hi connector phics ir DMI, on ays (sup port or DF 6x2160 (0x1200 (DDR4-2666 me R-2400 for low .OGb/s, 2.5", .OGb/s, 2.5", nigh, via USB gh, via USB or on system n processor, ne optional poports maxim or to DVI/HDM	2 MB / 4MB 2 MB / 4MB 3 MB / 4MB 4 MB / 4MB / 4MB / 4MB 4 MB / 4MB / 4MB / 4MB 4 MB / 4MB / 4	emory may clo memory control or 7200 rpm 3.00 x2 or PCI DD box DD box nemory, Direct and DP, or 2nd current HDM and Athlon / /	roller in processor le 3.0 x4 ectX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only		Kensington® MicroSaver® cable) • Smart USB protection, allows keyboard/ mouse only, blocks all storage devices • Power-on password • Administrator password Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Fingerprint Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black (only available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case • Toolless chassis open (need optional toolless chassis screw) • Toolless HDD, SSD, memory removal • Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration Optional VESA mount bracket kit, supports VESA 75mm and 100mm
Athlon Ryzen 3 Ryzen 5 Some: I	on PRO 300GE 3 PRO 2200GE 5 PRO 2400GE 5 PRO 3200GE 5 PRO 3400GE 5 PRO 3400GE max, DDR4-26 mb board support 1866, DDR4-213 ∴ Hard Drive / ∴ M.2 SSD (22 ∴ DVD-ROM, 9 ∴ MAS CORD TO Gra yPort™, one H pendent displa using HDMI pc rt 2 displays); esolution: 4090 nal DP to VGA	2/4 4/4 4/8 4/4 4/8 666*, tw ts up to E 83 or DDF SATA 6. 242 / 229 9.0mm hi connector phics in DMI, on ays (sup ort or DF	3.4 GHz 3.2 / 3.6 GHz 3.2 / 3.8 GHz 3.3 / 3.8 GHz 3.3 / 4.0 GHz 70 260-pin SC DDR4-2666 mg R-2400 for low 0Gb/s, 2.5", 80) / PCIe N' nigh, via USB por on system n processor, ne optional poports maxim p to DVI/HDN (DP) @60Hz;	1 MB / 4MB 2 MB / 4MB	DDR4-2666 DDR4-2933 DDR4-2933 DDR4-2933 DDR4-2933 DR4-2933 Exets, dual-chemory may clomemory control of 7200 rpm 3.0 x2 or PCI DD box DD box DD box DD box DD current HDM and Athlon / Amand Athlon / Ama	Radeon Vega 3 Radeon Vega 8 Radeon Vega 8 Radeon Vega 11 Radeon Vega 8 Radeon Vega 11 Radeon Vega 11 Radeon Vega 11 Radeon Vega 11 Rannel capable bocks down to roller in processor Ile 3.0 x4 PoctX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only	Mouse Mechanical	Administrator password Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Conly available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Ryzen 3 Ryzen 5 Ryzen S Ryzen	3 PRO 2200GE 5 PRO 2400GE 3 PRO 3200GE 5 PRO 3400GE 5 PRO 3400GE max, DDR4-26 m board support 1866, DDR4-213 ∴ Hard Drive / ∴ M.2 SSD (22 ∴ DVD-ROM, 9 ∴ DVD±RW, 9 ∴ DVD+RW, 9 ∴ DVD+RW, 9 ∴ DVD+RW, 9 ∴ DVD-RW,	4/4 4/8 4/4 4/8 666*, tw ts up to E 33 or DDF SATA 6. 242 / 222 9.0mm hi connector phics in DMI, on ays (sup ort or DF	3.2 / 3.6 GHz 3.2 / 3.8 GHz 3.3 / 3.8 GHz 3.3 / 4.0 GHz 70 260-pin SC DDR4-2666 me R-2400 for low .0Gb/s, 2.5", 80) / PCIe N' nigh, via USE gh, via USB ghr on system n processor, ne optional poports maxim to DVI/HDN (DP) @ 60Hz;	2 MB / 4MB 2 MB / 4MB 3 MB / 4MB 4 MB / 4MB / 4MB / 4MB 4 MB / 4MB / 4MB / 4MB 4 MB / 4MB / 4	DDR4-2933 DDR4-2933 DDR4-2933 DDR4-2933 Skets, dual-chemory may clomemory control of the control	Radeon Vega 8 Radeon Vega 11 Radeon Vega 8 Radeon Vega 8 Radeon Vega 11 nannel capable ocks down to roller in processor le 3.0 x4 ectX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only	Mouse Mechanical	Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black Conly available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Memory 32GB m * System DDR4-18 Disk Some: I Some: I Some: I Onboard SATA Graphics Monitor cable Monitor cable Chipset Front ports* (Std.) one USB Rear ports* (Opt.) Two opti * Depend Ryzen 5 Ryzen 5 Ryzen 5 Ryzen 5 Rozer 1 Some: I	5 PRO 2400GE 3 PRO 3200GE 5 PRO 3400GE max, DDR4-26 m board support 1866, DDR4-213 ∴ Hard Drive / ∴ M.2 SSD (22 ∴ DVD-ROM, 9 ∴ DVD±RW, 9	4/8 4/4 4/8 666*, tw ts up to E 83 or DDI SATA 6. 242 / 228 9.0mm hi 00mm hi 00mm hi 00mm connector phics ir DMI, on ays (sup ort or DF	3.2 / 3.8 GHz 3.3 / 3.8 GHz 3.3 / 4.0 GHz 70 260-pin SC DDR4-2666 me R-2400 for low .0Gb/s, 2.5", 80) / PCIe N' nigh, via USB gh, via USB gr on system n processor, ne optional poports maxim to DVI/HDN (DP) @60Hz;	2 MB / 4MB 2 MB / 4MB 2 MB / 4MB 2 MB / 4MB O-DIMM soc emory, and me ver capacity of 5400 rpm o VMe, PCIe 3 3 external OD external OD board uses main mort (VGA, 2n um of 2 condul dongles, a 4096x2160	DDR4-2933 DDR4-2933 DDR4-2933 DDR4-2933 Ekets, dual-chemory may clo memory contr or 7200 rpm 3.0 x2 or PCI DD box DD box memory, Direct dDP, or 2nd current HDM and Athlon / /	Radeon Vega 11 Radeon Vega 8 Radeon Vega 11 Rannel capable bocks down to roller in processor le 3.0 x4 actX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only	Mouse Mechanical	Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black (only available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Ryzen 3 Ryzen 5 Ryzen Synch Staten S Ryzen Synch S Ryzen Synch S Ryzen Synch S Ryzen Synch S Ryzen S Ryzen S Ryzen S Ryzen S R	3 PRO 3200GE 5 PRO 3400GE max, DDR4-26 m board support 1866, DDR4-213 : Hard Drive / : M.2 SSD (22 : DVD-ROM, 9 : DVD±RW, 9 :	4/4 4/8 666*, tw ts up to E 83 or DDI SATA 6. 242 / 222 3.0mm h 00mm higo connector phics ir DMI, on ays (sup ort or DF	3.3 / 3.8 GHz 3.3 / 4.0 GHz 70 260-pin SC DDR4-2666 me R-2400 for low .0Gb/s, 2.5", 80) / PCIe N' nigh, via USB gh, via USB or on system n processor, ne optional poports maxim P to DVI/HDN (DP) @60Hz;	2 MB / 4MB 2 MB / 4MB O-DIMM soc emory, and me ver capacity of 5400 rpm o VMe, PCIe 3 3 external OI external OD board uses main mort (VGA, 2n num of 2 cond VI dongles, a	DDR4-2933 DDR4-2933 DR4-2933 Ckets, dual-chemory may clo memory contr or 7200 rpm 3.0 x2 or PCI DD box DD box memory, Direct dDP, or 2nd current HDM and Athlon / /	Radeon Vega 8 Radeon Vega 11 nannel capable bocks down to roller in processor le 3.0 x4 actX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only	Mechanical	Some: Lenovo Calliope Mouse (USÉ connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black (only available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case • Toolless chassis open (need optional toolless chassis screw) • Toolless HDD, SSD, memory removal • Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Memory 32GB m * System DDR4-18 Disk Some: I Some: I Some: I Ontical Some: I Onboard SATA One SAT Graphics AMD Ra DisplayF 3 indepe when us support Max resi Monitor cable Optional HDMI 1. Chipset AMD B3 Front ports* (Std.) one USE one mice Rear ports* (Std.) Two opti * Depend	5 PRO 3400GE max, DDR4-26 m board support 1866, DDR4-213 ∴ Hard Drive / ∴ M.2 SSD (22 ∴ DVD-ROM, 9 ∴ DVD±RW, 9 . ATA 6.0Gb/s c Radeon™ Gra yPort™, one H pendent displa using HDMI po rt 2 displays); esolution: 40920 nal DP to VGA	4/8 666*, tw ts up to E 33 or DDI SATA 6. 242 / 222 9.0mm h 0omm higonometro phics in DMI, on ays (sup ort or DF 6x2160 (0x1200 (3.3 / 4.0 GHz o 260-pin SC DDR4-2666 me R-2400 for low OGb/s, 2.5", 80) / PCIe N' nigh, via USB gh, via USB or on system processor, ne optional poports maxim to DVI/HDN (DP)@60Hz;	2 MB / 4MB O-DIMM soc emory, and me er capacity of 5400 rpm o VMe, PCIe 3 8 external OD board uses main m ort (VGA, 2n num of 2 cond VI dongles, a	DDR4-2933 ckets, dual-chemory may clomemory control of 7200 rpm 3.0 x2 or PCI DD box DD box nemory, Director of DP, or 2nd current HDM and Athlon / /	Radeon Vega 11 nannel capable bocks down to roller in processor le 3.0 x4 actX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only	Mechanical	Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black (only available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Memory 32GB m * System DDR4-18 Disk Some: I Some: I Some: I Onboard SATA One SAT Graphics AMD Ra DisplayF 3 indepe when us support Max resi Monitor cable Chipset Chipset AMD B3 Front ports* (Std.) one USE none mice Rear ports* (Std.) Two opti Rear ports* (Opt.) Two opti * Depend	max, DDR4-20 m board support 1866, DDR4-213 : Hard Drive / : M.2 SSD (22 : DVD-ROM, 9 : DVD±RW, 9 . ATA 6.0Gb/s c Radeon™ Gral yPort™, one H pendent displa using HDMI po rt 2 displays); esolution: 4096 1920 nal DP to VGA	666*, tw ts up to E 33 or DDI SATA 6. 242 / 226 9.0mm hi connector phics ir DMI, on ays (sup port or DF 6x2160 (0x1200 (ro 260-pin SC DDR4-2666 me R-2400 for low .0Gb/s, 2.5", 80) / PCIe N' nigh, via USB gh, via USB or on system n processor, ne optional poports maxim to DVI/HDN (DP)@60Hz;	O-DIMM soc emory, and me rer capacity of 5400 rpm o VMe, PCIe 3 3 external OI external OD board uses main m ort (VGA, 2n um of 2 cond vil dongles, a	kkets, dual-chemory may clo memory control of 7200 rpm 3.0 x2 or PCI DD box DD box nemory, Direct do DP, or 2nd current HDM and Athlon / /	nannel capable ocks down to roller in processor le 3.0 x4 actX® 12, one di HDMI), supports MI/DVI displays Athlon PRO only		(only available via special bid models) Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case • Toolless chassis open (need optional toolless chassis screw) • Toolless HDD, SSD, memory removal • Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
* System DDR4-18 Disk Some: I	em board support 1866, DDR4-213 ∴ Hard Drive / ∴ M.2 SSD (22 ∴ DVD+ROM, 9. ∴ ATA 6.0Gb/s c Radeon™ Gra yPort™, one H pendent displa using HDMI po rt 2 displays); esolution: 4096 nal DP to VGA	ts up to E 33 or DDI SATA 6. 242 / 222 9.0mm h 0mm his connecto phics in DMI, on ays (sup prit or DF 6x2160 (0x1200 (DDR4-2666 me R-2400 for low .0Gb/s, 2.5", 80) / PCIe N' nigh, via USE gh, via USB or on system n processor, ne optional poports maxim 2 to DVI/HDM	emory, and me ver capacity of 5400 rpm o VMe, PCle 3 3 external OD external OD board uses main m ort (VGA, 2n lum of 2 con vll dongles, a	emory may clo memory control or 7200 rpm 3.00 x2 or PCI DD box DD box nemory, Direct and DP, or 2nd current HDM and Athlon / /	cks down to roller in processor le 3.0 x4 cctX® 12, one d HDMI), supports MI/DVI displays Athlon PRO only		Tiny (1L), black color; metal case Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Optical Some: I Some:	∴ M.2 SSD (22 ∴ DVD-ROM, 9 ∴ DVD±RW, 9 ∴ DVD±RW, 9 ∴ ATA 6.0Gb/s c Radeon™ Gral yPort™, one H pendent displa using HDMI po tt 2 displays); esolution: 4090 all DP to VGA	242 / 228 9.0mm histonnector phics in DMI, on ays (sup ort or DF 6x2160 (80) / PCIe Ninigh, via USE gh, via USE gh, via USE or on system processor, in e optional protts maximal to DVI/HDM (DP)@60Hz;	VMe, PCIe 3 3 external OI external OD board uses main m ort (VGA, 2n um of 2 cond vII dongles, a	3.0 x2 or PCI DD box DD box nemory, Dire nd DP, or 2nd current HDM and Athlon / /	ectX [®] 12, one d HDMI), supports dI/DVI displays Athlon PRO only		Optional dust filter M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Optical Some: I Some: I Some: I Some: I Some: I One SAT ONE SA	∴ DVD-ROM, § ∴ DVD+RW, 9. ∴ DVD+RW, 9. ∴ ATA 6.0Gb/s c Radeon™ Gra gyPort™, one H pendent display using HDMI port 2 displays); esolution: 4096 nal DP to VGA	9.0mm h 0mm hi connector phics in DMI, on ays (sup ort or DF 6x2160 (nigh, via USE gh, via USB or on system n processor, ne optional poports maxim to DVI/HDM (DP)@60Hz;	3 external OI external OD board uses main mort (VGA, 2n um of 2 condul dongles, a	DD box DD box nemory, Dire nd DP, or 2nd current HDM and Athlon / A	ectX [®] 12, one d HDMI), supports dI/DVI displays Athlon PRO only		M75q Tiny only: 7.0" W X 7.2" D X 1.5" H 179mm W X 183mm D X 37mm H 2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Onboard SATA One SAT Graphics AMD Ra DisplayF 3 indepe when us support Max res Monitor cable Optional HDMI 1. Chipset AMD B3 Front ports* (Std.) one USE none mice Rear ports* (Std.) 1x USB Rear ports* (Opt.) Two opti * Depend	ATA 6.0Gb/s c Radeon™ Gra yPort™, one H pendent displa using HDMI po rt 2 displays). esolution: 4096 1920 nal DP to VGA	phics in DMI, on ays (support or DF	or on system n processor, ne optional ports maxim to DVI/HDN (DP)@60Hz;	uses main mort (VGA, 2num of 2 conditional dongles, as 4096x2160	nemory, Dire nd DP, or 2nd current HDM and Athlon / /	d HDMI), supports II/DVI displays Athlon PRO only		2.91 lb (1.32 kg), weight may vary by configuration With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
Graphics AMD Ra DisplayF 3 indepe when us support Max res Monitor cable Chipset	Radeon™ Gra yPort™, one H pendent displa using HDMI po rt 2 displays); esolution: 4096 1920 nal DP to VGA	phics in DMI, on ays (suport or DF	n processor, ne optional poports maximo to DVI/HDN	uses main mort (VGA, 2num of 2 condul dongles, at 4096x2160	nd DP, or 2nd current HDM and Athlon / /	d HDMI), supports II/DVI displays Athlon PRO only		With VESA mount & ODD box: 7.42" W X 7.30" D X 2.48" H 188.4mm W X 185.38mm D X 63mm H 3.66 lb (1.66 kg), weight may vary by configuration
HDMI 1. Chipset AMD B3 Front ports* (Std.) one USE one mici Rear ports* (Std.) 1x USB Rear ports* (Opt.) Two opti * Depend	nal DP to VGA			7	(1 1DIVII) @ 30)Hz;	VESA mount Floor Stand	Optional system floor stand for vertical orientation
Front ports* (Std.) one USE one mici Rear ports* (Std.) 1x USB Rear ports* (Opt.) Two opti * Depend					to dual DP o	dongle, or DP to	Power supply	Some: 65 watts adapter, autosensing, 88% PSU (not included for TIO models) Some: 135 watts adapter, autosensing, 88% PSU (not included for TIO models)
Rear ports* (Std.) 1x USB Rear ports* (Opt.) Two opti * Depend	B300 Chipset						Limited warranty	10
	Front ports* (Std.) one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm) Rear ports* (Std.) 1x USB 3.1 Gen1, 3x USB 2.0, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI Rear ports* (Opt.) Two optional ports: Port 1 for VGA / 2nd DP / 2nd HDMI / serial; Port 2 for serial; * Depending on many factors, actual data transfer speed may be lower than theoretical speed						Preload	Preloaded operating system Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Some: Windows 10 IoT Enterprise Some: Linux Ubuntu
	Definition (HD)	Audio, F	Realtek ALC:	222CG / inte	ernal speake	er (1.5 watt)	Environment	ENERGY STAR® 7.1*, EPEAT™ Silver rating* (*Not for non-OS models); ErP Lot 3; RoHS-compliant; TUV low noise verified
Some:	Some: 11ac wireless, M.2 Card, Realtek RTL8822CE (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9260 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, 2x2 Some: Bluetooth 4.2 / 5.0 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Realtek RTL8111EPV-CG, Wake on LAN®						MIL-SPEC test	MIL-STD-810H military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock Fungus, Solar Radiation)
Some: Some: Some: I						,,	Accessories	For compatible accessories, please go to http://smartfind.lenovo.com
Manageability DASH 1.							1	











