# **OVERVIEW**





| 1. Thunderbolt 4                             | 5. USB 2.0                  |
|--|-----------------------------|
| 2. USB 3.2 Gen 1 (Always On)                 | 6. Ethernet (RJ-45) *       |
| 3. HDMI                                      | 7. Kensington Security Slot |
| 4. Headphone / microphone combo jack (3.5mm) |                             |

Notes:

• Ports with \* are only available on selected models

# PERFORMANCE

# **Processor**

## **Processor Family**

12th Generation Intel<sup>®</sup> Core<sup>™</sup> i3 / i5 / i7 Processor

## Processor\*\*[1]

| Processor<br>Name | Cores                       | Threads | Base Frequency                    | Max Frequency                     | Cache | Memory<br>Support | Processor<br>Graphics      |
|-------------------|-----------------------------|---------|-----------------------------------|-----------------------------------|-------|-------------------|----------------------------|
| Core i3-<br>1215U | 6 (2 P-core + 4<br>E-core)  | 8       | P-core 1.2GHz / E-<br>core 0.9GHz | P-core 4.4GHz / E-<br>core 3.3GHz | 10MB  | DDR4-3200         | Intel UHD<br>Graphics      |
| Core i5-<br>1235U | 10 (2 P-core +<br>8 E-core) | 12      | P-core 1.3GHz / E-<br>core 0.9GHz | P-core 4.4GHz / E-<br>core 3.3GHz | 12MB  | DDR4-3200         | Intel Iris® Xe<br>Graphics |
| Core i7-<br>1255U | 10 (2 P-core +<br>8 E-core) | 12      | P-core 1.7GHz / E-<br>core 1.2GHz | P-core 4.7GHz / E-<br>core 3.5GHz | 12MB  | DDR4-3200         | Intel Iris Xe<br>Graphics  |
| Core i5-<br>1240P | 12 (4 P-core +<br>8 E-core) | 16      | P-core 1.7GHz / E-<br>core 1.2GHz | P-core 4.4GHz / E-<br>core 3.3GHz | 12MB  | DDR4-3200         | Intel Iris Xe<br>Graphics  |
| Core i7-<br>1260P | 12 (4 P-core +<br>8 E-core) | 16      | P-core 2.1GHz / E-<br>core 1.5GHz | P-core 4.7GHz / E-<br>core 3.4GHz | 18MB  | DDR4-3200         | Intel Iris Xe<br>Graphics  |

#### Notes:

1. i5-1240P and i7-1260P are NOT available in EMEA.

Intel Iris Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel Iris Xe Graphics will function as Intel UHD Graphics.

# **Operating System**

# **Operating System**\*\*

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 Home 64 Single Language
- Windows 11 DG Windows 10 Pro 64
- Ubuntu Linux
- No operating system

# Graphics

## Graphics\*\*[1]

| Graphics                          | Туре       | Memory    | TGP           | Key Features |
|-----------------------------------|------------|-----------|---------------|--------------|
| Intel UHD Graphics                | Integrated | Shared    | Share CPU TDP | DirectX® 12  |
| Intel Iris Xe Graphics            | Integrated | Shared    | Share CPU TDP | DirectX 12.1 |
| NVIDIA <sup>®</sup> GeForce MX550 | Discrete   | 2GB GDDR6 | -             | DirectX 12   |

Notes:

1. Intel Iris Xe Graphics capability requires system to be configured with dual-channel memory. On the system with single-channel memory, Intel Iris Xe Graphics will function as Intel UHD Graphics.

# **Monitor Support**

## **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and Thunderbolt™)

- HDMI supports up to 3840x2160@60Hz
- Thunderbolt supports up to 5120x3200@60Hz

# Chipset

# Chipset

Intel SoC (System on Chip) platform

# Memory

## Max Memory<sup>[1]</sup>

- Up to 32GB DDR4-3200
- Up to 40GB (8GB soldered + 32GB SO-DIMM) DDR4-3200

#### Memory Slots\*\*

- One DDR4 SO-DIMM slot
- One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable

#### Memory Type

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

# Storage

#### Storage Support<sup>[1]</sup>

Up to two drives, 2x M.2 SSD

• M.2 2242 SSD up to 1TB

### Storage Slot

Two M.2 slots

- One M.2 2242 PCIe<sup>®</sup> Gen 3x4 slot, supports M.2 2242 SSD
- One M.2 2242 PCIe Gen 4x4 slot, supports M.2 2242 SSD

#### Storage Type

| Disk Type    | Interface               | Offering            | Security |
|--------------|-------------------------|---------------------|----------|
| M.2 2242 SSD | PCIe NVMe®, PCIe 4.0 x4 | 256GB / 512GB / 1TB | Opal2    |

Notes:

1. The storage capacity supported is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops.

# **Removable Storage**

Optical

#### None

**Card Reader** 

No card reader

# **Multi-Media**

## **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

#### Speakers

Stereo speakers, 2W x2, Dolby<sup>®</sup> Audio<sup>™</sup>, audio by HARMAN

#### Microphone

Dual array microphone, near-field

#### Camera\*\*

- HD 720p, with privacy shutter, fixed focus
- FHD 1080p, with privacy shutter, fixed focus
- IR & FHD 1080p hybrid, with privacy shutter, fixed focus

# **Battery**

## Battery\*\*

- Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr)
- Integrated Li-Polymer 57Wh battery

### Max Battery Life<sup>[1]</sup>

 Models with 45Wh battery: MobileMark<sup>®</sup> 2018: up to 9.4 hr

Lenovo

JEITA 2.0: up to 16.1 hr Local video (1080p) playback@150nits: up to 11.8 hr Models with 57Wh battery: MobileMark 2018: up to 11.5 hr MobileMark 25: up to 10.9 hr JEITA 2.0: up to 20.6 hr Local video (1080p) playback@150nits: up to 15.6 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

# **Power Adapter**

## Power Adapter\*\*[1]

- 65W USB-C<sup>®</sup> (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

Notes:

1. AC adapter offerings depend on the country.

# DESIGN

# Display

#### Display\*\*[1][2]

| Size  | Resolution         | Touch           | Туре | Brightness | Surface        | Aspect<br>Ratio | Contrast<br>Ratio | Color<br>Gamut | Viewing<br>Angle | Key<br>Features |
|-------|--------------------|-----------------|------|------------|----------------|-----------------|-------------------|----------------|------------------|-----------------|
| 14.0″ | FHD<br>(1920x1080) | None            | TN   | 250 nits   | Anti-<br>glare | 16:9            | 500:1             | 45%<br>NTSC    | 90°              | -               |
| 14.0″ | FHD<br>(1920x1080) | None            | IPS  | 300 nits   | Anti-<br>glare | 16:9            | 800:1             | 45%<br>NTSC    | 170°             | -               |
| 14.0″ | FHD<br>(1920x1080) | None            | IPS  | 300 nits   | Anti-<br>glare | 16:9            | 1200:1            | 100%<br>sRGB   | 170°             | -               |
| 14.0″ | FHD<br>(1920x1080) | Multi-<br>touch | IPS  | 300 nits   | Anti-<br>glare | 16:9            | 800:1             | 45%<br>NTSC    | 170°             | -               |

#### Touchscreen

- Capacitive-type on-cell multi-touch, supports 10-point touch
- Non-touch

Notes:

- 1. California Electronic Waste Recycling Fee
  - In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer
- 2. Multi-touch panel is only for special bid in EMEA.

# **Input Device**

## Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

## **Keyboard Backlight**

- LED backlight
- Non-backlight

## UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad, 57 x 100 mm (2.24 x 3.94 inches)

# **Mechanical**<sup>III</sup>

Lenovo

## Dimensions (WxDxH)

| Models                                     | Dimensions   |  |  |
|--|--|--|--|
| Aluminium (top), aluminium (bottom) models | 324 x 220.7 x 17.9 mm (12.76 x 8.69 x 0.7 inches)  |  |  |
| Aluminium (top), PC + ABS (bottom) models  | 324 x 220.7 x 18.9 mm (12.76 x 8.69 x 0.74 inches) |  |  |

#### Weight

| Models                                     | Weight                         |  |  |
|--|--------------------------------|--|--|
| Aluminium (top), PC + ABS (bottom) models  | Starting at 1.59 kg (3.51 lbs) |  |  |
| Aluminium (top), aluminium (bottom) models | Starting at 1.64 kg (3.62 lbs) |  |  |

#### Case Color\*\*[2]

- Black
- Mineral metallic

#### Case Material\*\*

- Aluminium (top), aluminium (bottom)
- Aluminium (top), PC + ABS (bottom)

#### Notes:

1. The system dimensions and weight vary depending on configurations.

2. Mineral metallic case is NOT available in EMEA.

# CONNECTIVITY

## **Network**

#### Ethernet

- Gigabit Ethernet, Intel Ethernet Connection I219-V, 1x RJ-45, supports Wake-on-LAN
- No Ethernet

## WLAN + Bluetooth®\*\*[1][2]

- Wi-Fi<sup>®</sup> 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Wi-Fi 6E, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- AMD RZ616, Wi-Fi 6E, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card
- Realtek Wi-Fi 6 RTL8852BE, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.1, M.2 card
- Intel Wi-Fi 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card
- Intel Wi-Fi 6E AX211, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 Card

## WWAN

No support

#### SIM Card

No SIM card inbox

#### NFC

No support

## Notes:

- 1. Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitation
- 2. 6GHz Wi-Fi 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi 6E, and the regional regulatory certifications & spectrum allocation.
- Wi-Fi 6E is only enabled on Windows 11 and operates as Wi-Fi 6 with Windows 10.

# **Ports**<sup>III</sup>

#### Standard Ports

- 1x USB 2.0
- 1x USB 3.2 Gen 1 (Always On)
- 1x Thunderbolt 4 / USB 4 40Gbps (support data transfer, Power Delivery 3.0, and DisplayPort™ 1.4)
- 1x HDMI, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

# **Optional Ports**

1x Ethernet (RJ-45)

#### Notes:

- 1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;
  - USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
  - USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
  - USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
  - Thunderbolt 3/4: 40 Gbit/s

# Docking

# Docking

Various docking solutions supported via Thunderbolt. For more compatible docking solutions, please visit <u>Docking for ThinkPad® E14 Gen 4 (Intel)</u>

# **SECURITY & PRIVACY**

# Security

## Security Chip\*\*

- Firmware TPM 2.0 integrated in SoC
- Discrete TPM 2.0, TCG certified

## Physical Locks

Kensington<sup>®</sup> Security Slot<sup>™</sup>, 3 x 7 mm

## Smart Card Reader

No smart card reader

#### Fingerprint Reader

- Touch style fingerprint reader on power button
- No fingerprint reader

## **BIOS Security**

- Power-on password
- Supervisor password
- NVMe password

# Self-healing BIOS

#### **Other Security**

- Camera privacy shutter
- (Optional) IR camera for Windows Hello

# SERVICE

# Warranty

## Base Warranty\*\*[1]

- 1-year mail-in service
- 1-year depot service
- 1-year depot with 2-year system board service (Korea only)
- 1-year limited onsite service
- No base warranty

#### Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

# **ENVIRONMENTAL**

# **Operating Environment**

## Temperature<sup>[1][2]</sup>

• Operating: 5°C (41°F) to 35°C (95°F)

Lenovo

- Storage and transportation in original shipping package: -20°C (-4°F ) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

### Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

## Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

2. When you charge the battery, its temperature must be no lower than 10°C (50°F).

# ACCESSORIES

# **Bundled Accessories**

## **Bundled Accessories**

- Lenovo 15.6" laptop casual toploader, polyester, grey
- None

# CERTIFICATIONS

# **Green Certifications**

## Green Certifications

- EPEAT<sup>™</sup> Gold
- ENERGY STAR<sup>®</sup> 8.0
- ErP Lot 3
- TCO Certified 9.0RoHS compliant

# **Other Certifications**

Mil-Spec Test MIL-STD-810H military test passed

Other Certifications

TÜV Rheinland<sup>®</sup> Low Blue Light (Software Solution)

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



intel



intel





intel

intel

intel

intel