

 <p>Monitors Commercial</p>	<p>V196LBmd <i>Bright colors, sustainable vision</i></p>  
<p>Sub Model Product line</p>	<p>V196LB V6 Series</p>
<p><i>General</i></p>	
<p>Display Type Dimensions (WxHxD mm) Min. Profile Thickness mm Net Weight (kg) Gross Weight (kg) Chassis colour and finish</p>	<p>Flat screen/TFT 406.4x422.7x191 19.5 3.1 4.46 Black Matt</p>
<p><i>Display</i></p>	
<p>Panel Technology Crystalbrite Size cm Size Inch Format Display dimensions (mm) Pixel Pitch (mm) Resolution Frequency (H/V) PPI Rsp time (ms) Dynamic Contrast ratio Brightness (cd/m2) H/V° CR 10:1 H/V° CR 5:1 Colors Bit Color Gamut Backlight type Screen coating hardness OS Compliance</p>	<p>IPS No 48 19 5:4 375x300 0.294 1280x1024@60HzHz 30-80kHz/55-75Hz 86 5 100M:1 250 178/178 178/178 16.7M 6Bit+Hi-FRC 72% NTSC LED 3H Win10 compliant</p>
<p><i>Video Input</i></p>	
<p>Input Signal</p>	<p>VGA + DVI (w/HDCP)</p>
<p><i>Audio Input</i></p>	
<p>Speaker</p>	<p>1Wx2</p>
<p><i>Ergonomics</i></p>	
<p>VESA Wall Mounting Kensington Support Tilt Swivel degrees Hgt Adj (mm) Pivot degrees</p>	<p>100x100 Yes -5°~25° No No No</p>
<p><i>Power Supply</i></p>	
<p>Power Supply Energy Star Type Off/Standby (W) Sleep (W) Min On (W) Max (W) EEL Class Power On (W) Annual Energy Consumption (kWh/year) Mercury (mg) Lead</p>	<p>Internal ES7.0 0.14 0.3 15.8 - - - - 0 Presence*</p>
<p><i>Manufacturer Guarantee</i></p>	
<p>Warranty Certificates Certification MTBF Hours @ 25°C</p>	<p>EMEA Commercial (3yr) CE, TÜV GS, ISO9241-307 class II TCO7.0 30000</p>
<p><i>Pallet and Container Loading</i></p>	
<p>Pallet qty (pcs) Pallet Size (WxHxD) cm Container loading 20"/40" Package Dimensions (cm) Included cables</p>	<p>110 108.8x108.8x120 1100/2200 50.2x11.6x42.0 VGA</p>
<p><i>Special Features</i></p>	
<p>Wide Viewing Angle Comfyview</p>	<p>Wide Viewing Angle Comfyview</p>