
Key **Features**

Stunning 4K Ultra HD Resolution | SuperClear PS Panel Technology |
HDR10 Content Support | Frameless Design | Next Generation
Connectivity



Product **Description**

Whether for office use or for enjoying entertainment at home, the ViewSonic* VX2776-4K-mhd is designed to take your viewing experience to another level. With a SuperClear* IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Stunning 4K Ultra HD resolution delivers 4-times more pixels than Full HD monitors, which boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. Moreover, HDR10 content support delivers vivid colors and brightness that exceed standard monitors. Built-in HDMI and DisplayPort inputs deliver flexible connectivity options for a wide range of devices.



Menu Control Panel Internal Speakers HDMI (x2) DisplayPort AC In Kensington® Lock Slot



Audio Out









Display: Display Size (in.): 27 Viewable Area (in.): 27 Panel Type: IPS Resolution: 3840 x 2160 4K (3840x2160) Resolution Type: Static Contrast Ratio: 1,300:1 Dynamic Contrast Ratio: 80,000,000:1 Light Source: WLED 350 cd/m2 Brightness: Colors: 1.07B Color Space Support: 8-bit+Hi-FRC

Aspect Ratio: 16:9 Response Time (Typical GTG): 14ms Response Time (GTG w/OD): 4ms

178° horizontal, 178° vertical Viewing Angles:

Backlight Life (Hours): 30,000

Panel Surface: Anti-glare, Hard coating (3H)

Compatibility:

PC Resolution (max): 3840 x 2160

Connector:

3.5mm Audio Out(1), HDMI 2.0(2), Display Port(1)

Audio:

Internal Speakers: 2.5W (x2)

Power:

34W Eco Mode (Conserve): Eco Mode (optimized): 39W 44W Consumption (typical): Consumption (max): 48W

AC 100-240V (universal), 50-60Hz Voltage:

0.5W Stand-by:

Additional Hardware:

Kensington Lock Slot:

Controls:

Physical Controls: 1,2,3,4,Power

Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) On Screen Display:

Operating Conditions:

32-104° F (0 - 40° C) Temperature:

20-90% Humidity (non-condensing):

Mount:

VESA Compatible: 100 x 100 mm

Video Signal:

15 ~ 160 KHz Frequency Horizontal: Frequency Vertical: 40 ~ 75 Hz

Video Input:

TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2) Digital Sync:

Ergonomics:

Tilt (Forward/Back): 3° / 20°

Weight (imperial):

Net (lbs): 12.3 Net Without Stand (lbs): 11.0 Gross (lbs): 15.4

Weight (metric):

Net (kg): 5.6 Net Without Stand (kg): 5.0 Gross (kg): 7.0

Dimensions (imperial) (WxHxD):

Packaging (in.): 27.4 x 18.2 x 5.2 Physical (in.): 24.3 x 17.8 x 7.2 Physical Without Stand (in.): 24.3 x 14.4 x 1.8

Dimensions (metric) (WxHxD):

Packaging (mm): 697.0 x 462.0 x 132.0 616.0 x 451.0 x 184.0 Physical (mm): Physical Without Stand (mm): 616.0 x 366.0 x 46.0

Regulations: MX-CoC, Mexico Energy, CE, CE EMC, CB, Energy Star compliant PACKAGE CONTENTS: VX2776-4K, Power Cable, HDMI Cable, Quick Start Guide Recycle/Disposal: Please dispose of in accordance with local, state or federal laws. Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907995817

Accessories:

CB-00008948, CB-00010555, CB-00010684, CB-00010958, LCD-CMK-001, LCD-DMA-001, LCD-DMA-002, LCD-WMK-001

Copyright © ViewSonic Corporation 2000-2019. All rights reserved. (07/08/2019 02:07 AM PST)