

# W400+

Bright, powerful and small

---



- **Bright WXGA projector – 4000 ANSI lumens**
- **Installation flexibility – 1.3x zoom**
- **Ultimate Control - Full support for Crestron, Extron, AMX, PJ-Link and Telnet LAN commands**
- **Easy connectivity - HDMI, VGA, USB Power, 10W speaker, RJ45**

Experience excellence with the first ever 4,000 lumen, small, lightweight W400+ projector. This model is designed to be used at any time for multiple purposes including professional use- from classrooms to business meetings. Designed to replace legacy LCD projectors with a similar throw, it offers top quality projected colours, long lamp life with a low overall cost of ownership.♂♂

This HD ready product has fantastic external sound from built-in speakers, providing you with a more immersive experience. Additionally, it boasts simplicity in design with multiple inputs including HDMI/MHL, USB Power and RJ45 networking. This projector is ideal for connecting dongles such as the Google Chromecast and the Optoma HD-Cast Pro. This lightweight projector allows you to connect your laptop, PC or Blu-ray player and can either be installed or conveniently taken on the move.

# Specifications

<b>Display/image</b>	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	4,000 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction - vertical	+/-40°
Horizontal scan rate	15.3 ~ 91.1Khz
Vertical scan rate	24 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.92m - 7.65m (36.1in - 301.1in)(Diagonal)
<b>Lamp info</b>	
Light source	Lamp
Lamp watts	220
Lamp life (hours)	5000 (Bright), 6500 (Dynamic), 6000 (Eco), 7000 (Eco+), 10000 (Education)
Lamp life (education)	10,000 hours
<b>Optical</b>	
Throw ratio	1.19:1 - 1.54:1
Projection distance (m)	1.2m - 12m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	16.91 ~ 21.6
Native offset	112%
<b>Connectivity</b>	
Connections	<b>Inputs</b> 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a 3D support, 2 x VGA (YPbPr/RGB), 1 x Composite video, 1 x S-Video <b>Outputs</b> 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A power 1A <b>Control</b> 1 x RS232, 1 x RJ45
<b>General</b>	
Noise level (typical)	29dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D compatibility	Full 3D
3D	Security bar,Kensington Lock,Password protected interface
OSD / display languages	25 languages: Arabic,Czech,Danish,Dutch,English,Farsi,Finnish,French,German,Greek, (simplified),Spanish,Swedish,Chinese (traditional),Turkish,Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Data remote with laser and mouse function
Speaker count	1
Watts per speaker	10W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual
<b>Power</b>	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption (standby)	0.5W
Power consumption (min)	204W
Power consumption (max)	266W
<b>Weight and dimensions</b>	
Net weight	2.5kg
Dimensions (W x D x H) (mm)	298 x 230 x 96

