

Key **Features**

- 1ms Response Time
- SuperClear® IPS technology
- AMD FreeSync™ technology
- Full HD 1080p resolution
- Ergonomically Designed for Gamers



Product **Description**

The ViewSonic ELITE XG2405 is a 24" IPS-panel gaming monitor with 1ms response time, a 144Hz refresh rate, and AMD FreeSync technology, providing the perfect blend of speed, hyper-responsive control, and vivid IPS colours. Engineered for hardcore and casual gamers alike, the XG2405's sleek, 3-side borderless, ergonomic design make it the ideal choice for any gaming setup.

Visit Us — www.viewsonic.com

DISPLAY	
Display Size (in.):	24
Viewable Area (in.):	23.8
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	80M:1
Light Source:	LED
Brightness:	250 cd/m2 (typ)
Colours:	16.7M
Colour Space Support:	8 bit (6 bit + Hi-FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	1ms
Viewing Angles:	178º horizontal, 178º vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	144
Adaptive Sync:	FreeSync
Blue Light Filter:	Yes
Flicker-Free:	Yes
Colour Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.275 mm (H) x 0.275 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)
COMPATIBILITY	
PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10 certified; macOS tested
Mac® Resolution (min):	1920x1080
3.5mm Audio Out:	1
HDMI 1.4:	2
Display Port:	1
Power in:	3-pin Socket (IEC C14 / CEE22)
AUDIO	
Internal Speakers:	2Watts x2
POWER	
Eco Mode (Conserve):	17W
Eco Mode (Optimised):	21W
Consumption (typical):	24W
Consumption (max):	30W
Voltage:	AC 100-240V, 50/60 Hz
Stand-by:	0.5W
Power Supply:	Internal
ADDITIONAL HARDWARE	
Kensington Lock Slot:	1
Cable Organisation:	Yes
CONTROLS	

VIDEO INPUT	
Digital Sync:	TMDS - HDMI (v1.4), PCI-E - DisplayPort (v1.2)
ERGONOMICS	
Height Adjust (mm):	120
Swivel:	90°
Tilt (Forward/Back):	-5° / 20°
Pivot (Right/Left):	90° / 0°
WEIGHT (METRIC)	
Net (kg):	6.7
Net Without Stand (kg):	3.4
Gross (kg):	8.4
DIMENSIONS (METRIC) (WXHXD)	
Packaging (mm):	699 x 402 x 182
Physical (mm):	540 x 521 x 239
Physical Without Stand (mm):	540 x 325 x 43
GENERAL	
	CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UkrSEPRO,
Regulations:	BSMI, RCM, GEMS, VCCI, PSE, KC, e-Standby, BIS, CCC, China RoHS, CEL
PACKAGE CONTENTS:	e-Standby, BIS, CCC, China RoHS,
Ü	e-Standby, BIS, CCC, China RoHS, CEL XG2405 x1, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-

Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)

Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

32°F to 104°F (0°C to 40°C)

20% to 90%

100 x 100 mm

30 ~ 180KHz

47 ~ 144Hz

Physical Controls:

On Screen Display:

Temperature:

WALL MOUNT
VESA Compatible:

INPUT SIGNAL

Frequency Horizontal:

Frequency Vertical:

OPERATING CONDITIONS

Humidity (non-condensing):