CLOUDSPEED

SanDisk[.]

6Gb/s SATA Data Center SSD

CloudSpeed Eco[™] Gen. II SATA SSD

Hyperscale Data Center Flash Storage

Features

- Capacity offerings: 1.92TB, 960GB, and 480GB
- Highly-Reliable Data Throughput: 530MB/s sequential read performance
- Optimized for Read-Intensive application workloads
- Low power consumption compared to traditional HDDs
- Data loss protection with power failure protection
- Includes the innovative Guardian Technology[™] Platform for improved flash endurance and data integrity & protection
- MTBF = 2 Million Hours

Specialized for the following workloads:

- Social Media
- Web Servers
- Content Repositories
- Video on Demand (VoD)
- Media Streaming
- Analytics, NoSQL, and Data Warehousing
- Web-based Applications

Evolving Cloud Storage Requirements and Data Growth

SaaS, laaS, and PaaS business models are evolving to support enterprises for "mission-critical" type of infrastructure and applications. Consumers expect 24/7 access to cloud services and apps for entertainment and personal productivity.

For cloud service providers, the "mission-critical" nature of cloud services creates opportunities for higher performance tiers of service based on flash storage. In order to serve the new demands of cloud services, flash storage will have to perform with reliable throughput, data integrity & protection mechanisms, and better flash endurance.

Cloud Service Providers must also balance the insatiable appetite for data storage capacity at higher tiers of service without degradation to performance or storage cost overruns.

To help enable cloud service providers deliver richer data services and apps, while addressing growing data capacity demands, SanDisk offers a SATA SSD specifically designed for hyperscale environments.

CloudSpeed Eco[™] Gen. II SATA SSD - Specifically Designed for Hyperscale Data Centers

For a complete balance of storage capacity scale with data center features for "mission-critical" type of data services, CloudSpeed Eco Gen. II SATA SSDs, with up to 2TB* of capacity, serves demanding tiers of service at multi-petabyte capacity levels.

This flash storage SATA SSD works within existing infrastructure – SATA interface – and replaces hard disk drives (HDDs) for an overall lower total cost of ownership (TCO) and benefits of greater storage density.



CloudSpeed Eco™ Gen. II 2.5″ SATA SSD Preliminary specifications subject to change		
Performance		
Interface	SATA 6Gb/s	
Sequential Read/Write (MB/s)**	Up to 530/460 MB/s ¹	
Random Read/Write (IOPS)	Up to 76K/14K IOPS ²	
Capacity		
15nm MLC User Capacities*	480GB, 960GB and 1.92TB	
Reliability		
Data Reliability (BER)	1 unrecoverable error in 10 ^{18*****} read ³	
MTBF***	2 Million Hours	
Data Fail Recovery	Flexible Redundant Array of Independent Memory Elements (FRAME) Technology	
Power Fail Recovery	Write cache immunity with in-flight data protection	
Temperature Monitoring	S.M.A.R.T. warning with performance throttling	
Warranty****	The lesser of 5 years or maximum endurance used	
Endurance		
DWPD (Random/Workload)****	0.6 DWPD ⁵ for 5 years	
Power		
Vcc	5.0V +10%/-5%	
Active (Typ)	3.8W avg. sequential write, 2.6 avg. sequential read	
Idle	1.6W RMS	
Environmental		
Shock (operating)	1000g @ 1.0 msec, 1 shock along each axis, X, Y, Z, in each direction	
Vibration (operating)	3.22 g rms, 5-1,000Hz	
Operating Temperature	0° C to 70° C (internal)	
Storage Temperature	-40° C to 85° C	
Humidity	5% to 95%, non-condensing, relative humidity ⁴	
Altitude	(operating) -1,000 feet to 15,000 feet	
Mechanical		
Length	100.2 mm	
Width	69.85 mm	
Height	7.17 mm	
(1) Based on a 128KB transfer rate, using Oakgate SVE exerciser		

(2) Based on 4/KB transfer rate using Oakgate SVG exerciser (3) The JEDEC 64.8 specification requires 1 in 10⁹ for enterprise-class SSDs (4) Based on MIL-STD 810-F, Method S07.4 (5) Endurance based on 100% 4K random workload

CloudSpeed Eco™ Gen. II 2.5″ SATA SSD - Ordering Information	
Part Number	Capacity
SDLF1DAR-480G-1Hxx	480GB
SDLF1DAR-960G-1Hxx	960GB
SDLF1CRR-019T-1Hxx	1.92TB

xx - Pack Out Option: OEM/Hyperscale: A1 Channel: A2

For more information, please visit:

www.sandisk.com/enterprise

datacentersales@sandisk.com

Milpitas, CA 95035-7933, USA

Contact information

SanDisk Corporation 951 SanDisk Drive

T: 1-800-578-6007

SanDísk[®]

At SanDisk, we're expanding the possibilities of data storage. For more than 25 years, SanDisk's ideas have helped transform the industry, delivering next generation storage solutions for consumers and businesses around the globe.

Specifications subject to change without notice. 1 GB = 1,000,000,000 bytes. Actual user capacity less. **Up to stated speed. Based on internal testing: performance may vary depending upon drive capacity, host device, OS and application. 1 megabyte (MB) = 1 million bytes. **MTBF - Mean Time Between Failures based on parts stress analysis. ***Waranty/DWPD - The lesser of 5 years from the date of manufacture of the product or the date on which the product's relevant endurance thresholds set forth in the product specifications are reached. *****1 recoverable error in 10[®].

©2016 SanDisk Corporation. All rights reserved. SanDisk is a trademark of SanDisk Corporation, registered in the United States and other countries. CloudSpeed Eco and Guardian Technology are trademarks of SanDisk Corporation. Other brand names mentioned herein are for identification purposes only and may be the trademarks of their holder(s). CloudSpeed Eco Gen.II Datasheet 03.14.16