

## **Key Features**

Extended Lifespan | Automatic Sleep Timer | Auto Power Off | Bright Images in Any Environment | Amazing Color Accuracy



## Product **Description**

The ViewSonic PA503X offers impressive visual performance to improve presentations, ideal for use in small business meeting rooms and classrooms. Packed with 3600 ANSI Lumens of brightness and a 22,000:1 contrast ratio, this projector is guaranteed to reproduce the finest of details regardless of the amount of ambient lighting present. ViewSonic exclusive SuperColor™ technology offers a wider range of displayable color for projected images with true-to-life color accuracy. Users can choose from 5 color modes, including standard, brightest, presentation, photo, and movie mode, to select the mode that best suits their needs based on their usage scenario. In addition, the energy-saving SuperEco mode of PA503X reduces power consumption and extends the lamp life by up to 15,000 hours.



- 1. Keypad
- 2. LED indicator
- 3. Lamp cover 4. Security lock
- 5. Zoom/Focus
- 6. Front IR
- 7. Projection Lens
- 8. Audio in/out
- 9. HDMI
- 10. Dual VGA
- 11. VGA out
- 12. Mini USB
- - 13. Video
  - 14. Kensington® Lock Slot
  - 15. RS232

Visit Us www.viewsonic.com

SPECIFICATION			
Projection system:	0.55" XGA		
Native Resolution:	1024x768		
DC type:	DC3		
Brightness:	3600 ANSI Lumens		
Contrast Ratio with SuperEco mode:	22000:1		
Display Color:	1.07 Billion Colors		
Light Source:	Lamp		
Light source life (Nor/SuperEco):	5000/15000		
Lamp Watt:	190W		
Lens:	F=2.56-2.68, f=22-24.1 mm		
Projection Offset:	120%+/-5%		
Throw Ratio:	1.96~2.15		
Image size:	30" - 300"		
Throw Distance:	1.19m-13.11m(100" @3.98m)		
Keystone:	±40° (Vertical)		
Optical Zoom:	1.1x		
Audible Noise (Eco):	27dB		
Resolution Support:	VGA(640 x 480) to FullHD(1920 x 1080)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K~102KHz		
Vertical Scan Rate:	23~120Hz		
INPUT			
Computer in (share with component):	2		
Composite:	1		
Audio-in (3.5mm):	1		
HDMI:	1 (Back)		
ОИТРИТ			
Monitor out:	1		
Audio out (3.5mm):	1		
Speaker:	2W		
CONTROL			
RS232:	1		

USB type mini B (Services):

## **OTHERS**

	Power Supply Voltage:	100-240V+/- 10%, 50/60Hz AC
	Power Consumption:	Normal: 260W Standby: <0.5W
	Operating Temperature:	0~40°C
	Carton:	Brown
	Net Weight:	2.2kg
	Dimensions (WxDxH) w/adjustment foot:	294x218x110mm
	Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
	STANDARD ACCESSORY	
	Power Cord:	1
	VGA cable:	1
	Remote Control:	1
	QSG & CD:	QSG: 1 / CD: NA
OPTIONAL ACCESSORY		
	Air Filter:	RSPL