Key Features

Fit For Classrooms of All Sizes | Discrete
Wireless Multimedia Content Streaming |
Easy Image Adjustment | SuperColor™:
Best in Class Color Accuracy | Enlarged
Speaker for Enhanced Sound



Product **Description**

For schools that need to project large, high-quality images from within a short distance, ViewSonic PS700W ultrashort throw projector is the perfect solution. With the ability to project 87″ images from a distance of only 9.1cm* from the projection surface, the projector is flexible enough to fit any classrooms installation and keeps the projection beam clear of out of sight and eliminating image shadows for distraction-free classroom application. With the design of the PortAll® concealed compartment, PS700W provides more flexibility when using wireless dongles and PC sticks and allowing teachers to present more interesting lesson content. The best in class color accuracy of SuperColor™ Technology produces vibrant color, while SonicExpert® and SonicMode technologies deliver room-filling sound quality. *Actual distances may vary depending on environmental conditions





- 1. Lamp cover
- 2. Projection Lens
- 3. LED indicator 4. IR remote sensor
- 5. Air filter
- 6. Focus

- 7. Keypad
- 8. USB 9. Mini USB
- 10. AC in
- 11. HDMI
- 12. S Video/Composite
- 13. Audio in/out
- 14. Dual VGA
- 15. RS232
- 16. VGA out
- 17. LAN
- 18. Kensington® Lock Slot

SPECIFICATION	
Projector system:	0.65" WXGA (1280x800)
Brightness:	3300 ANSI Lumens
Contrast Ratio with Sleep Mode:	10000:1
Light Source:	Lamp
Lamp Hour (Nor./SuperEco):	3000/6000
Lamp Watt:	240W
Offset:	130%±5%
Throw Ratio:	0.23
Keystone:	HV
Optical Zoom:	Fixed
Audible Noise (Normal/Eco):	35dB / 29dB
Speaker:	10W x 2 cube
Interactive Solution:	No
INPUT	
Computer in (D-SUB 15 pin):	2
Composite:	1
S-video:	1
Audio-in (3.5mm):	1
Audio-in (RCA R/L):	1
HDMI:	1 (Back)
HDMI/MHL:	1 (PortAII)
OUTPUT	
Monitor out (D-SUB 15 pin):	1
Audio out (3.5mm):	1
USB type A (Power):	2 (5V2.4A) 1x Back, 1x PortAll
CONTROL	
RS232:	1
RJ45:	1
USB type mini B (Services):	1
DIMENSIONS AND POWER	
Dimension (Net):	434x388x153mm
Weight (Net):	6.1kg
Power Voltage:	100~240Vac 50/60Hz
Power Consumption:	410W (Max.)
STANDARD ACCESSORY	
Power cord:	1 or 2 (vary by region)
VGA cable:	1
Remote Control:	1 (w/laser pointer)
QSG & CD:	QSG: 1 / CD: 1
Carton:	Brown
OPTIONAL ACCESSORY	
Warranty Card:	Yes (CN Only)

LANGUAGES

On Screen Display:

English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese

REGULATIONS

TUV-S Mark(Argentina), FCC,CE EMC,CB,,CCC, ROHS, REACH, SVHC, WEEE, ErP, Mexico NOM, cTUVus, RCM

WARRANTY

**Warranty offered may differ from market to market

Yes (CN Only)

Air Filter: