

Key **Features**

Bright Images Anywhere | Amazing Color Accuracy | Bring the Excitement of Game Day to Life | Immersive 3D Viewing | Enhanced Gaming Experience



Product **Description**

PX700HD is a 3500 ANSI lumens Full HD 1080p DLP projector that offers impressive visual performance in brightly lit environments. This projector comes equipped with ViewSonic's exclusive SuperColor™ technology which delivers true-to-life colors, as well as a specialized Sports Mode which enhances colors to make sporting events feel more realistic. In addition, PX700HD can be placed into SuperEco mode to reduce power consumption and extend the lamp life to up to 15,000 hours. Dual HDMI inputs allow users to connect multiple devices and share content in high-definition, while the integrated USB power supply can be used as a power source for connected devices.





SPECIFICATION		OTHERS	
Projection system:	0.47" 1080p	Power Supply Voltage:	100-240V+/- 10%,
Native Resolution:	1920x1080		50/60Hz AC 0~40°C
DC type:	DC3	Operating Temperature: Carton:	
Brightness:	3500 ANSI Lumens		Brown
Contrast Ratio:	12000:1	Dimensions (WxDxH) w/adjustment foot:	332x261x135mm
Display Color:	1.07 Billion Colors	Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese
Light Source:	Lamp		
Light source life (Normal):	5000/15000		
Lamp Watt:	203W		
Lens:	F=2.0~2.05,f=15.843mm~17.445mm		
Projection Offset:	110%+/-6%	STANDARD ACCESSORY	
Throw Ratio:	1.5-1.65	Power Cord:	1
Image size:	30" - 300"	VGA cable:	1
Throw Distance:	1m~10.96m (100"@3.32m)	Remote Control:	1
Keystone:	±40° (Vertical)	QSG:	1
Optical Zoom:	1.1x	OPTIONAL ACCESSORY	
Audible Noise (Eco):	27dB	Lamp/Light Source:	RLC-116
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p		
Video Compatibility:	NTSC, PAL, SECAM		
Horizontal Frequency:	15K~102KHz		
Vertical Scan Rate:	23~120Hz		
INPUT			
Computer in (share w component):	vith 1		
Audio-in (3.5mm):	1		
HDMI/HDCP:	2 (HDMI 1.4/ HDCP 1.4)		
OUTPUT			
Monitor out:	1		
Audio out (3.5mm):	1		
Speaker:	2W		
USB type A (Power):	1 (5V/1.5A)		
CONTROL			
RS232:	1		
USB type mini B (Ser	rvices): 1		