
Key Features

- 1ms MPRT response time
- · Adaptive Sync technology
- 93% NTSC & 131% sRGB colour size
- QHD 1440p resolution
- Dual HDMI and DisplayPort inputs



Product **Description**

The ViewSonic VX2758-2KP-mhd is a 27" QHD monitor that provides remarkable speed and vivid colours. Designed with QHD (2560 x 1440) resolution and 93% NTSC, 131% sRGB colour size, this monitor displays more on-screen content that meets and exceeds industry colour standards. With a 144Hz refresh rate, 1ms MPRT response time and Adaptive Sync support, the VX2758-2KP-mhd delivers unprecedented screen quality and speed. Flexible connectivity via DisplayPort and two HDMI ports make connection to other peripherals or high-end graphics cards for gaming a breeze. The monitor features a user-customised ViewMode to instantly activate the most suitable mode with precalibrated colour and luminance for each scenario, such as Game mode or Movie mode. Additionally, it comes with Flicker-Free and Blue Light Filter eye-care technology for a reliable and sincere commitment to our users' health.*This monitor is GeForce Driver G-Sync Enable-Ready[Disclaimer].



Internal Speakers
VESA Compatible (Wall Mount 100x100mm)
Menu Controls
4 AC In
Earphone
DisplayPort

Visit Us www.viewsonic.com

7. HDMI X 2

LCD PANEL		POWER		DIMENSIONS (IMPERIAL) (WXHXD)	
Display Size (in.):	27	Eco Mode (Conserve):	32W	Packaging (in.):	26.6 x 1
Viewable Area (in.):	27	Eco Mode (optimised):	35W	Physical (in.):	24.2 x 1
Panel Type:	IPS Technology	Consumption (typical):	38W	Physical Without Stand (in.):	24.2 x 1
Resolution:	2560 x 1440	Consumption (max):	43W	DIMENSIONS (METRIC) (WXHXD)	
Resolution Type:	QHD	Voltage:	AC 100-240V, 50/60 Hz	Packaging (mm):	675 x 4
Static Contrast Ratio:	1,000:1 (typ)	Stand-by:	0.5W	Physical (mm):	615 x 4
Dynamic Contrast Ratio:	80M:1	Power Supply:	Internal	Physical Without Stand (mm):	615 x 3
Light Source:	LED	ADDITIONAL HARDWARE		GENERAL	
Brightness:	350 cd/m2 (typ)	Kensington Lock Slot:	1		CTUVus CoC, Mc CB, Rol
Colours:	1.07B	Cable Organisation:	N/A	Regulations:	
Colour Space Support:	10 bit (8 bit + FRC)	CONTROLS			EAC, U
Aspect Ratio:	16:9	Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4,	PACKAGE CONTENTS:	VX2758 (IEC C1 (v2.0; M Guide x
Response Time (Typical GTG):	3ms		Key 5, Key 6 (power)		
Response Time (GTG w/OD):	3.8ms	On Screen Display:	Input Select, Audio Adjust, ViewMode, Colour Adjust, Manual Image Adjust, Setup Menu	Recycle/Disposal:	Please
Response Time (MPRT):	1ms	OPERATING CONDITIONS		, ,	local, st
Viewing Angles:	178° horizontal, 178° vertical	Temperature:	32°F to 104°F (0°C to 40°C)	Warranty:	*Warrar market
Backlight Life (Hours):	30000 Hrs (Min)	Humidity (non-condensing):	20% to 90%	Country Of Origin:	China
Curvature:	Flat	WALL MOUNT	2011 10 0011		
Refresh Rate (Hz):	144	VESA Compatible:	100 x 100 mm		
Adaptive Sync:	FreeSync	INPUT SIGNAL			
Blue Light Filter:	Yes	Frequency Horizontal:	30 ~ 240KHz		
Flicker-Free:	Yes	Frequency Vertical:	48 ~ 146Hz		
X Lighting:	N/A	VIDEO INPUT			
Colour Gamut:	DCI-P3: 96% size (Typ) NTSC: 93% size (Typ) sRGB: 131% size (Typ)	Digital Sync:	TMDS - HDMI (v1.4), TMDS - HDMI (v2.0), PCI-E - DisplayPort (v1.2)		
Pixel Size:	0.233 mm (H) x 0.233 mm (V)	ERGONOMICS			
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Height Adjust (mm):	N/A		
COMPATIBILITY	rum Glare, mana Goalling (Gir)	Swivel:	N/A		
PC Resolution (max):	2560x1440	Tilt (Forward/Back):	-5° / 15°		
Mac® Resolution (max):	2560x1440	Pivot (Right/Left):	N/A		
PC Operating System:	Windows 10 certified; macOS tested	WEIGHT (IMPERIAL)			
Mac® Resolution (min):	2560x1440	Net (lbs):	11.6		
CONNECTOR		Net Without Stand (lbs):	9.7		
3.5mm Audio Out:	1	Gross (lbs):	15.5		
HDMI 2.0:	1	WEIGHT (METRIC)			
HDMI 1.4:	1	Net (kg):	5.3		
Display Port:	1	Net Without Stand (kg):	4.4		
Power in:	3-pin Socket (IEC C14 / CEE22)	Gross (kg):	7.1		
AUDIO	. () - : : :)				
Internal Speakers:	2.5Watts x2				

26.6 x 17.7 x 6.

24.2 x 17.7 x 7.

24.2 x 14.4 x 2

675 x 450 x 174 615 x 450 x 189

615 x 365 x 50

cTUVus, FCC-B CoC, Mexico Er CB, RoHS, ErP, EAC, UkrSEPR

VX2758-2KP-M (IEC C13 / CEE (v2.0; Male-Mal

*Warranty offere

market to marke

Guide x1 Please dispose local, state or fe