

Data Sheet FUJITSU Display B27-8 TS Pro

Advanced Widescreen 69 cm (27 inch) Performance Display Ideal for document management applications in the workplace

The FUJITSU Display B27-8 TS Pro is an Advanced Widescreen display with 1920 x 1080 resolution that can accomodate two A4 sized documents side-by-side with ease making it ideal for document management applications in the workplace. The display delivers consistent picture quality and has a range of connectivity options ideal for medium- and large-sized businesses.

27-inch with 16:9 aspect ratio at Full HD resolution for consistent clarity and superior viewing experience ideal for office applications

5-in-1 stand base with cable guide that allows users to tilt, swivel, adjust height and rotate monitor display as per their comfort and working style

Thin bezel housing on three sides for multi-monitoring scenarios, integrated speakers and cable guide for a clean desk approach

DisplayView™ Software enables you to configure your monitor for adjusting screen brightness, pivot function and much more

Environmental-friendly LED technology with highly efficient energy saving functions like ECO Operation mode and ECO standby helping you save on costs

Always available USB, DisplayPort, HDMI interfaces ensure you have a complete package that meets all your business requirements













Technical details

n-Plane Switching (IPS) technology, Low blue light mode, 5-in-1 Stand, Cable guide, Eco button for Eco mode and 3-coloured Eco status LED, Always available USB (in operating and standby mode), DisplayView™ Software, 24/7 usage, Integrated speakers 5-in-1 Stand 130 mm 40 mm 90° 15° / +35° 345° n-Plane Switching (IPS) technology/LED Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1 16.7 million colors (Hi-FRC)
5-in-1 Stand 130 mm 40 mm 90° .5° / +35° 345° n-Plane Switching (IPS) technology/LED Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
130 mm 40 mm 90° -5° / +35° 845°
130 mm 40 mm 90° -5° / +35° 845°
40 mm 90° -5° / +35° -345°
Poo° 15° / +35° 1845° In-Plane Switching (IPS) technology/LED Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
n-Plane Switching (IPS) technology/LED Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 1,78°/178° CR10:1
n-Plane Switching (IPS) technology/LED Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 1,78°/178° CR10:1
n-Plane Switching (IPS) technology/LED Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
Anti-glare, 3H hard coating 1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
1,000:1 20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
20,000,000:1 5 ms (in Video mode) 178°/178° CR10:1
5 ms (in Video mode) 178°/178° CR10:1
178°/178° CR10:1
16.7 million colors (Hi-FRC)
300 cd/m ²
16:9
58.6 cm (27-inch)
1,920 x 1,080 pixel
1,680 x 1,050 pixel, 1,440 x 900 pixel, 1,280 x 1,024 pixel, 1,280 x 720 pixel, 1,024 x 768 pixel, 800 x 600 pixel, 640 x 480 pixel
597 x 336 mm
0.311 mm
30 - 82 kHz
56 - 76 Hz
210 Mhz
1 x DisplayPort
1 x HDMI 1.4
1 x D-SUB
3.5 mm stereo phone jack for head phone
3.5 mm stereo phone jack
2 x 2 W
2 x USB 3.1 (Gen 1)
1 x USB 3.1 (Gen1)
1 X 000 5.11 (delity
Brightness, ECO, Input, Mode, Audio, Menu
Arabic, Czech, Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Japanese, Chinese traditional, Chinese simply
Brightness, Contrast, Black level, Auto level, ACR
SRGB, Office, Photo, Video, Low Blue Light
sRGB, 5000K, 6500K, 7500K, Native, Custom Color (R,G,B)
Language, OSD-Timeout, OSD rotation
58 1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,1,

Image adjust	Clock, Phase, H-Position, V-Position, Expansion
Audio	Mute, Volume, Input for HDMI and DP interface
Information	Model name, Serial number, Signal input, Resolution/mode, Display mode, Color Temperature, ACR Status
Advanced settings	Overdrive, DDC/CI, Factory Recall
Power consumption (typical)	
Soft switch off	0.27 W
Power save mode	0.32 W
Operating with EPA settings	18 W
Total Energy Consumption (ETEC)	57.1 kWh/year
Operating maximum brightness	25 W
Power supply	integrated
Power notes	Speakers off, USB not connected ETEC and EPA refer to ENERGY STAR® 7.0
Electrical values	
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Protection class	1
Compliance	
Europe	Energy Efficiency Class: A+, EN 60950, CE certification according to EC Directive 2004/108/EEC, RoHS, WEEE, IT-Eco-Declaration
Model	B27-8T
Germany	TÜV GS
Russia	EAC
USA/Canada	FCC Class B, cUL
Saudi Arabia	SASO
Global	ENERGY STAR® 7.0, TCO Certified Displays 7.0, EPEAT® Gold (dedicated regions), Zero bright and dark pixel faults, Subpixel faults according to ISO9241-307 (Pixel fault class I), TÜV Flicker Free Certified, TÜV Low Blue Light Certified
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	621.3 x 62.8 x 368.9 mm
	24.46 x 2.47 x 14.52 inch
Dimension with stand $(W \times D \times H)$	621.3 x 269.4 x 388 mm
	24.46 inch x 10.61 x 15.28 inch
Weight (packed)	8.7 kg
	18.19 lbs
Weight (unpacked)	6.72 kg
	14.81 lbs
Weight (Monitor only)	4.34 kg
	9.57 lbs
Operating ambient temperature	5 - 35 °C (41 - 95 °F)
Operating relative humidity	10 - 85 % (non condensing)
Miscellaneous	
Miscellaneous	VESA DDC/ CI, Flat Display Mounting Interface VESA MIS-D 100 C, Kensington lock prepared
Color	Matt black
Package content	
Display delivered accessories	DisplayPort data cable 1.8 m USB-cable 1.8 m (USB-A to USB-B) Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8 m Quickstart flyer Safety notes
Display delivered accessories notes	Power cable with IEC-60320-C13, 3-pin connector on display side Data cables and USB cable detachable on display User manual and DisplayView Software is available via download

Order information	
Order Code	S26361-K1641-V160
EAN Code	4059595631584
Accessories information	Further helpful options: Stands and Mounting kits: http://www.fujitsu.com/fts/products/computing/peripheral/accessories/desktop/ums/index.html Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/Publications/public/pos-connectivity.pdf
Warranty	
Warranty period	3 years (depending on country)
Warranty type	Collect & Return Service (depending on country specific requirements)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu products, solutions & services

In addition to FUJITSU Display B27-8 TS Pro, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Display B27-8 TS Pro, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/fts/displays

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html

Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2019-01-18 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright 2019 Fujitsu Technology Solutions GmbH