


750 / 1050W

Snow Silent



Special Features

- Ultra High Efficiency, 80 PLUS® Platinum Certified
- Seasonic Patented DC Connector Panel with Integrated Voltage Regulation Module
- 120 mm Fluid Dynamic Bearing (FDB) Fans
- New Seasonic Hybrid Silent Fan Control – S³FC
- Highly Reliable 105°C Aluminum Electrolytic Capacitors
- Ultra Tight Voltage Regulation



Power Distribution

| Model | +3.3 V | +5 V | +12 V | -12 V | +5 Vsb | Total Power |
|------------------|--------|------|--------|-------|--------|-------------|
| Snow Silent-750 | 25 A | 25 A | 62 A | 0.5 A | 3 A | 750 W |
| | 125 W | | 744 W | 6 W | 15 W | |
| Snow Silent-1050 | 25 A | 25 A | 87 A | 0.5 A | 3 A | 1050 W |
| | 125 W | | 1044 W | 6 W | 15 W | |



Snow Silent-750

Wire Configuration

| Model | Main Power (20P / 24P) | EPS12V / ATX12V (8P / 4P) | EPS12V (8P) | PCI-E (6P / 8P) | SATA | Peripheral (4P) | FDD(4P) |
|------------------|------------------------|---------------------------|-------------|-----------------|------|-----------------|---------|
| Snow Silent-750 | 1 | 1 | 1 | 4 | 10 | 5 | 1 |
| Snow Silent-1050 | 1 | 1 | 1 | 8 | 14 | 5 | 1 |



Snow Silent-1050

Safety and EMI / EMC



*1050 W model only

Protection Features: OPP / OVP / SCP / UVP / OCT / OTP

Dimension: Snow Silent-750: 170 mm (L) x 150 mm (W) x 86 mm (H)

Snow Silent-1050: 190 mm (L) x 150 mm (W) x 86 mm (H)



Specifications may change without prior notice



Headquarters Tel: +886-2-2659-0338 Fax: +886-2-2659-0530 sales@seasonic.com.tw www.seasonic.com

USA Tel: +1 626-969-9966 Fax: +1 626-969-9986 usa@seasonic.com www.seasonicusa.com

Europe info@seasoniceu.com

Japan Tel: +81-3-6805-4085 japan@seasonic.com